

# Ordering information continued.

For drive units with F-coupling



Sales No.	Product	ø / length mm	Volume ml	max. Tip speed m/s
<b>W «W-DESIGN» - FOR FIBROUS / STRINGY MATERIALS</b>				
11030301	PT-DA 12/2WEC-F154	12/154	3 - 250	14
11030304	PT-DA 20/2WEC-F193	20/193	20 - 2000	22
11030294	PT-DA 20/2WEG-F210*	20/210	20 - 2000	30
11030309	PT-DA 30/2WEC-F250	30/250	100 - 4000	30
11030345	PT-DA 30/2WMEC-F250**	30/250	100 - 4000	30
11030319	PT-DA 36/2WEC-F250	36/250	200 - 4500	34
11030346	PT-DA 36/2WMEC-F250**	36/250	100 - 4500	34
11030324	PT-DA 40/2WEC-F250	40/250	200 - 5000	36
11030328	PT-DA 45/2WEC-F250	45/250	200 - 6000	40
11030334	PT-DA 50/2WEC-F250	50/250	300 - 10000	44
11030342	PT-DA 60/2WEC-F250	60/250	300 - 30000	50




<b>Z «Z-DESIGN» - FOR PILLS AND HARD / BRITTLE SAMPLES</b>				
11030310	PT-DA 30/2ZEC-F250	30/250	100 - 4000	14
11030067	PT-DA 12/2ZMEC-E157*	12/157	2 - 250	12

\*Z-Design aggregate with knives



<b>B «BIOTRONA® -DESIGN» - HIGH-TURBULENCE MIXING</b>				
11030355	PT-DA 07/BEC-F101	07/101	10 - 100	7
11030354	PT-DA 12/BEC-F154	12/154	50 - 500	12
11030296	PT-DA 20/BEC-F193	20/193	20 - 2000	21
11030314	PT-DA 36/BEC-F250	36/250	500 - 10000	34
11030326	PT-DA 45/BEC-F250	45/250	300 - 30000	40



<b>D «DISSOLVER-DESIGN»</b>				
11030344	PT-DA 30/DEC-F250	30/250	500 - 10000	30
11030337	PT-DA 53/DEC-F250	53/250	800 - 30000	47
11030343	PT-DA 65/DEC-F250	65/250	1000 - 40000	50



<b>TiN «TITANIUM NITRATED» - UPGRADE</b>				
11035050	TiN rotor for the selected dispersing aggregate			ø 12 - 36 mm
11035150	TiN stator for the selected dispersing aggregate			ø 12 - 36 mm



<b>G «GAS TIGHT - WITH SINGLE MECHANICAL SEAL» FOR PRESSURE / VACUUM</b>				
11030295	PT-DA 20/2G-F210	20/210	20 - 2000	22
11030306	PT-DA 30/2G-F273	30/273	100 - 4000	30
11030312	PT-DA 30/4G-F273	30/273	100 - 4000	30
11030316	PT-DA 36/2G-F273	36/273	200 - 4500	34
11030318	PT-DA 36/4G-F273	36/273	200 - 4500	34
11030321	PT-DA 40/2G-F273	40/273	200 - 5000	36
11030327	PT-DA 45/2G-F273	45/273	200 - 6000	40
11030331	PT-DA 50/2G-F273	50/273	300 - 10000	44
11030336	PT-DA 50/6G-F273	50/273	300 - 10000	44
11030339	PT-DA 60/2G-F273	60/273	300 - 30000	50