Exhaust Filters & Mufflers

Standard Exhaust Filters & Directional Exhaust Filters



1417P-10

- Filters oil mist from pump exhaust
- Easy replacement of element
- Reduces pump noise
- Filters to 0.3 micron particle size
- Screw-in type

t from	Standard Exhaust Filters						
st	Use with	Dimensions, inches		Filter	Replacement Element		
ment	Pump Model	Diameter	Height	CAT. No.	CAT. No.		
	8890 ^{1.} , 8905, 1399, 1400, 1400N	2.5"	2.5"	1417	1417L (2 pk)		
np noise	8907, 8912, 8917	2.5"	4.5"	1417P-7	1417R		
micron	8920, 8925, 1376, 1402, 1405, 1402N, 1376N	5.0"	6.25"	1417P-10	1417G		
	1397, 1374	5.0"	9.0"	1417P-20	1417H-01		
Э	8917A-80, 8947C-80	2.5"	4.5"	1417P-7	1417R		

Note: 1. GEM® (8890) includes 1417 as standard equipment.



1417A

- Large, high capacity
 360° Swivel outlet with tubing connector
- Screw-in type
- Continuously separates oil mist from the vacuum pump exhaust and by gravity returns the oil to the pump.

	Directional Exhaust Filters							
		Dimensions, inches				Gasket		
Use w Pump	rith Model	Diameter		Outlet Tube O.D.	Filter CAT. No.	Element CAT. No.	Replacement CAT. No.	
8925,	8912, 8917, 8920, 1376,1380, 1402, 1402N, 1376N	5.0"	7.5"	1.0"	1417A	1417G	1417A-01	
8907,	8912, 8917	6.5"	10.0"	2.0"	1417B	1417H	1417B-01	

Exhaust Oil Recycler



Exhaust Mist Eliminator shown installed on pump with oil return line.

Exhaust oil recyclers are recommended for vacuum systems with continuous pressure of 1 torr (1mm Hg) or higher.^{1.} At these pressures, conventional exhaust filters quickly saturate. The Mist Eliminator System continuously separates oil mist from the vacuum pump exhaust and actively returns the oil to the pump.

CAT. No.	Vacuum Pump Model No.
1416B	8890 (GEM®)
1416H	8905
1416C	8907, 8912, 8917, 8920, 8925
1416H-01	1400, 1400N
1416C-01	1376, 1376N, 1402, 1402N, 1405

Note: 1. *CAUTION:* Two stage vane vacuum pumps such as models 8905, 8907, 8912, 8920, 8917, 8925, 1400, 1402, 1376, 1405, 1400N, 1402N and 1376N should not be operated continuously at pressures above 10torr.

Hermetically Sealed Oil Mist Eliminators



When attached to an effective exhaust line, the hermetically sealed oil mist eliminator prevents corrosive vacuum pump exhaust gases from escaping into the room. It also coalesces oil mist from the pump exhaust and allows it to drain back into the pump. Coalescing the oil mist prevents loss of oil and the frequent need to add expensive vacuum fluids. Stainless steel construction with borosilicate microfiber element and fluoroelastomer gaskets. Requires, but does not include pump adapter kit. Dimensions of CAT. No. 1416D: 5"Wx7-3/4"H; 1416F, 5"Wx13-3/8"H. 1416D exhaust port accepts 13/16" I.D. hose.

			Replacement Element CAT. No.
1400N	1416D	1416E-01	1417Y-05
1402N, 1376N	1416D	1416E-02	1417Y-05

Welch-Ilmvac