

3675 / 3676 3679N / 691N / 692 3671N

Introduced more than 20 years ago, Jenco's basic inline meters continue to be the go-to choice for unparalleled ease-of use and reliability. These no-frills pH/mV (ORP) inline meters perform continuous on-location monitoring and remote monitoring and control, optimizing your mission-critical processes by increasing quality and reducing downtime.

Specifications

Page.64



3675



3676



3679N



691N



692



3671N



Parameters	pH & ORP	pH & ORP	pH & ORP	pH	pH	pH & ORP & Temp
Range	0.00 ~ 14.00 pH (pH) ±1999 mV (ORP)	0.00 ~ 14.00 pH (pH) ±1999 mV (ORP)	0.00 ~ 14.00 pH (pH) ±1999 mV (ORP)	0.00 ~ 14.00 pH	0.00 ~ 14.00 pH	0.0 ~ 14.0 pH (pH) ±1990 mV (ORP)
Resolution	0.01 pH (pH) 1 mV (ORP)	0.01 pH (pH) 1 mV (ORP)	0.01 pH (pH) 1 mV (ORP)	0.01 pH	0.01 pH	0.1 pH (pH) 10 mV (ORP)
Accuracy	±0.05 pH (pH) ±0.5% F.S. (ORP)	±0.05 pH (pH) ±0.5% F.S. (ORP)	±0.03 pH (pH) ±0.1% F.S. (ORP)	±0.05 pH	±0.05 pH	±0.1 pH ± 1 digit (pH) ±0.1% F.S. ± 1 digit (ORP)
Temp Range	0 ~ 100 °C	0 ~ 100 °C	0 ~ 100 °C	0 ~ 100 °C	0 ~ 100 °C	0 ~ 100 °C
Temp Resolution	NA	NA	NA	NA	NA	1 °C
Temp Accuracy	NA	NA	NA	NA	NA	±1 °C ± 1 digit
Calibration	Up to 2 points	Up to 2 points	Up to 2 points	Up to 2 points	Up to 2 points	Up to 2 points
pH Buffer Recognition	USA , NIST	USA , NIST	USA , NIST	USA , NIST	USA , NIST	USA , NIST
ATC	Auto	Auto	Auto	Manual	Auto	Auto
Temperature Sensor	PT100	PT100	PT100	NA	PT100	PT100
Screen	Segment LCD	LED	Segment LCD	LED	Segment LCD	LED
Control	2 Relay	2 Relay	2 Relay	NA	NA	2 Relay
Relay Output	5 A at 115 VAC or 2.5 A at 220 VAC	5 A at 115 VAC or 2.5 A at 220 VAC	5 A at 115 VAC or 2.5 A at 220 VAC	NA	NA	5 A at 115 VAC or 2.5 A at 220 VAC
Relay Output(Resistive load only)	4 ~ 20 mA (isolated)	4 ~ 20 mA (isolated)	4 ~ 20 mA (isolated)	4 ~ 20 mA (isolated)	4 ~ 20 mA (isolated)	NA
Analog Output	450 Ω	450 Ω	450 Ω	600 Ω	600 Ω	NA
Current Output Max Load	115 or 230 VAC , 50/60 Hz	115 or 230 VAC , 50/60 Hz	115 or 230 VAC , 50/60 Hz	115 or 230 VAC , 50/60 Hz	115 or 230 VAC , 50/60 Hz	115 or 230 VAC , 50/60 Hz
Power Supply	NA	NA	IP65	NA	NA	NA
Waterproof	96 X 96 X 119 mm	96 X 96 X 119 mm	96 X 96 X 119 mm	96 X 96 X 119 mm	96 X 96 X 119 mm	96 X 96 X 119 mm