

Bag sealer "S-400-B"

SUITABLE FOR POLYPROPYLENE-POLYESTER STERILISING BAGS WITH A PAPER BASE.

FEATURES

CONTROL PANEL

Front part made of metal epoxy covered case.

Illuminated mains switch.

Pressure sealer. Manual cut.



Part No.	Seal Width	Maximum seal	Height / Width / Depth	Power	Weight
	mm	length mm	(exterior) cm	W	Kg
4100047	12	300	17,5 47 35	100	4.8





Bag sealer "Seal-1000"

FOR POLYPROPYLENE AND POLYESTER BAGS WITH A STERILE PAPER BASE.

FEATURES

Metal construction with stainless steel

Pressure sealer unit with lateral leaver with two bilateral cutting edges. Constant sealing temperature (from 180 °C and 200 °C).

External support for rolls of up to 240mm wide, with adjustable separator sides to accommodate different roll sizes.

CONTROL PANEL

Illuminated start switch.

Indicator, optimum seal temperature.

Part No.	Seal width	Maximum seal	Height / Width / Depth	Power	Weight
	mm	length mm	(exterior) cm	W	Kg
4101712	10	260	30 36 43	400	6.5





Automatic bag sealer "Seal-Com 2" ACCORDING TO DIN 58953 SECTION 7 STANDARD. FOR POLYPROPYLENE-POLYESTER BAGS WITH PAPER BASE TO STERILIZE. CONTI-NUOUS SEALING. MANUAL OR AUTOMATIC ADVANCE.

Continuous Thermosealer

FEATURES

Exterior in enamel protected steel. Heating time: 4'. Sealing width: 10 mm. Sealing speed: 6 m / min. Acoustic signal of cycle starting. Electronic regulation and digital reading of temperature.

CONTROL PANEL

Start-up light switch. Manual or automatic start switch.



MODEL

Part No.	Height / Width / Depth	Power	Weight
	(sealer) cm	W	Kg
4100044	16 48 26	720	13

