

SUITABLE FOR POLYPROPYLENE-POLYESTER STERILISING BAGS WITH A PAPER BASE.

FEATURES

CONTROL PANEL Illuminated mains switch.

Front part made of metal epoxy covered case. Pressure sealer. Manual cut.

MODEL

Part No.	Seal Width mm	Maximum seal length mm	Height / (ext	Width erior) o	•	Power W	Weight Kg
4100047	12	300	17,5	47	35	100	4.8





Bag sealer "Seal-1000"

FOR POLYPROPYLENE AND POLYESTER BAGS WITH A STERILE PAPER BASE.

FEATURES

Metal construction with stainless steel tray.

Pressure sealer unit with lateral leaver with two bilateral cutting edges. Constant sealing temperature (from 180 °C and 200 °C).

External support for rolls of up to 240mm wide, with adjustable separator sides to accommodate different roll sizes.

CONTROL PANEL

Illuminated start switch. Indicator, optimum seal temperature.

Part No.	Seal width	Maximum seal	Height / Width / Depth	Power	Weight
	mm	length mm	(exterior) cm	W	Kg
4101712	10	260	30 36 43	400	6.5





Automatic bag sealer "Seal-Com 2" ACCORDING TO DIN 58953 SECTION 7 STANDARD. FOR POLYPROPYLENE-POLYESTER BAGS WITH PAPER BASE TO STERILIZE. CONTI-NUOUS SEALING. MANUAL OR AUTOMATIC ADVANCE.

Continuous Thermosealer

FEATURES

Heating time: 4'.

Sealing width: 10 mm. Sealing speed: 6 m / min. Acoustic signal of cycle starting. Electronic regulation and digital rea-

ding of temperature.

Exterior in enamel protected steel.

CONTROL PANEL

Start-up light switch. Manual or automatic start switch.



NEW

MODEL

Part No.	Height / Width / Depth (sealer) cm	Power W	Weight Kg	
4100044	16 48 26	720	13	

