

FPW55-SL Ultra-Low Refrigerated / Heating Circulator

The Ultra-Low Refrigerated Circulators of the HighTech Series with HL or SL circulator feature powerful pressure and suction pumps. The instruments provide the entire variety of functions of the professional HighTech Series of circulators.

Product features

- VFD COMFORT DISPLAY
- LCD DIALOG DISPLAY backlit for convenient interactive operation
- Keypad for setpoints, warning/safety values and menu functions
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- TCF Temperature Control Features to optimize the control behavior
- ATC3 3-Point-Calibration
- Pt100 External sensor connection for measurement and control
- SMART PUMP, electronically adjustable pump stages
- Unique early warning system for low liquid level
- Adjustable high temperature cut-out, visible via display
- RS232/RS485 interface for online communication
- Integrated programmer for 6 x 60 program steps
- Connections for solenoid valve and HSP booster pump
- Proportional cooling control
- Active Cooling Control



Performance values

400V/3PNPE/50Hz (Plug 32A CEE)	
Heating capacity kW	3
Viscosity max. cSt	70
Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4
Power consumption A	20

Order No.	9352756.07				
Cooling capacity (Ethanol)					
°C	20	0	-20	-40	-50
kW	5.2	4.1	2.2	0.7	0.3
* Performance specifications measured in accordance with DIN 12876. Cooling capacities up to 20 °C measured with ethanol; over 20 °C with thermal oil unless otherwise specified. Performance specifications apply at an ambient temperature of 20 °C. Performance values may differ with other bath fluids.					
Refrigerant stage 1					
Refrigerant	R452A				
Filling weight g	850				
Global Warming Potential for R452A	2140				
Carbon dioxide equivalent t	1.819				

Technical data

Available voltage versions		Bath	
Order No.	9 352 756	Bath cover	integrated
Available voltage versions:		Usable bath opening cm (W x L / D)	28 x 23 / 23
9352756.16	208V/3PPE/60Hz (Without Plug) (R452A)		
9352756.07	400V/3PNPE/50Hz (Plug 32A CEE) (R452A)		
Cooling		Other	
Cooling of compressor	1-stage Water	Classification	Classification III (FL)
Cooling water temperature max. °C	20	IP Code	IP 21
Cooling water pressure max. bar	6		
Cooling water difference pressure bar	3.5		
Cooling water consumption l/min	6.6		
Electronics		Dimensions and volumes	
Interfaces	Profibus optional	Weight kg	146
External pt100 sensor connection	integrated	Cooling Water Connection in	G $\frac{3}{4}$
Integrated programmer	6x60 steps	Dimensions cm (W x L x H)	59 x 76 x 116
Temperature control	ICC	Filling volume l	27
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values		Included in delivery	
Setting the resolution of the temperature display °C	0.01	2 Barbed fittings for tubing 8 and 12 mm ID. (Pump connections M16x1 male)	
Working temperature range °C	-55 ... +100	2 each barbed fittings for tubing 8 and 12 mm inner dia. (pump connections M16x1 female).	
Temperature stability °C	±0.05		
Ambient temperature °C	+5 ... +40		
Temperature display resolution °C	0.01		

All Benefits



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of ± 0.05 °C.



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



Condensation and ice protection
A heated cover plate prevents condensation or ice build-up in the bath



Connection of additional equipment
Stakei connections for solenoid valve, HSP booster pump and HST booster heater



Control of the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines