

FPW91-SL Ultra-Low Refrigerated / Heating Circulator

The Ultra-Low Refrigerated Circulators of the HighTech Series with HL or SL circulator feature powerful pressure and suction pumps. The instruments provide the entire variety of functions of the professional HighTech Series of circulators.



Product features

- VFD COMFORT DISPLAY
- LCD DIALOG DISPLAY backlit for convenient interactive operation
- ICC (Intelligent Cascade Control), self-optimizing temperature control
- TCF Temperature Control Features to optimize the control behavior
- ATC3 3-Point-Calibration
- SMART PUMP, electronically adjustable pump stages
- Adjustable high temperature cut-out, visible via display
- RS232/RS485 interface for online communication
- Integrated programmer for 6 x 60 program steps
- Connections for solenoid valve and HSP booster pump
- Proportional cooling control

Performance values

400V/3PNPE/50Hz (Plug 63A CEE)	
Heating capacity kW	3
Viscosity max. cST	70
Pump capacity flow rate l/min	22 ... 26
Pump capacity flow pressure bar	0.4 ... 0.7
Maximum suction bar	0.2 ... 0.4
Power A	32

Order No.	9352793.07					
Cooling capacity (Ethanol)						
°C	20	0	-20	-40	-60	-80
kW	4.5	4.1	3.7	3.1	2	0.75
Refrigerant stage 1			Refrigerant stage 2			
Refrigerant	R404A		Refrigerant	R23		
Filling volume g	900		Filling volume g	1000		
Global Warming Potential for R404A	3922		Global Warming Potential for R23	14800		
Carbon dioxide equivalent t	3.53		Carbon dioxide equivalent t	14.8		

Technical data

Available voltage versions		Bath	
Order No.	9 352 793	Bath cover	integrated
Available voltage versions:		Usable bath opening cm (W x L / D)	28 x 23 / 20
9352793.16	230V/3PPE/60Hz (Without Plug) (R404A)		
9352793.07	400V/3PNPE/50Hz (Plug 63A CEE) (R404A)		
Cooling		Other	
Cooling of compressor	2-stage Water	Classification	Classification III (FL)
Cooling water temperature max. °C	20	IP Code	IP 21
Cooling water pressure max. bar	6		
Cooling water difference pressure bar	3.5		
Cooling water consumption l/min	7.5		
Electronics		Dimensions and volumes	
Digital interface	Profibus optional	Weight kg	303
External pt100 sensor connection	integrated	Cooling Water Connection in	G¾
Integrated programmer	6x60 steps	Dimensions cm (W x L x H)	85 x 76 x 116
Temperature control	ICC	Filling volume l	22
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values			
Setting the resolution of the temperature display °C	0.01		
Working temperature range °C	-91 ... +100		
Temperature stability °C	±0.2		
Ambient temperature °C	+5 ... +40		
Temperature display resolution °C	0.01		

All Benefits



100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.
Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.
Highest standards of quality for a long product life.



Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Intelligent temperature control.
Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of +/- 0.05 °C.



Connection of additional equipment
Stakei connections for solenoid valve, HSP booster pump and HST booster heater



Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function



Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages



For flammable bath fluid
Classification III (FL) according to DIN 12876-1



Process. Under control.
Full regulation of the dynamics control, access to all important control parameters for individual process optimization.



100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines



Condensation and ice protection
A heated cover plate prevents condensation or ice build-up in the bath



Control of the external application
External Pt100 sensor connection for precise measurement and control directly in the external application



ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.