

FT902 FT immersion cooler

JULABO immersion coolers are primarily used for counter-cooling when connected to a heating circulator, or for rapidly cooling fluids down to low temperatures. Take advantage of the space-saving design.

JULABO immersion coolers represent an economical alternative to conventional tap water cooling. The easy-to-use units are suitable for a variety of cooling applications.

Product features

- Rapid cooling of liquids down to low temperatures
- Counter-cooling of liquids in combination with heating circulators
- · Preventing the use of precious tap water for cooling
- Compact design, small footprint
- · Ease of operation
- · Dry ice substitution



Performance values

Order No.			9650892.03				
Cooling capa	city (Ethanol)						
°C	20	10	0	-20		-40	-80
kW	0.3	0.27	0.27	0.24		0.2	0.07
Refrigerant stage 1			Refrigerant stage 2				
Refrigerant		R404A		Refrigerant		R23	
Filling volume g		310		Filling volume g		65	
Global Warming Potential for R404A		3922		Global Warming Potential for R23		14800	
Carbon dioxide equivalent t		1.216		Carbon dioxide equivalent t		0.962	

Technical data

Available voltage versions		Cooling	
Order No.	9 650 892	Cooling of compressor	2-stage Air
Available voltage versions:			
9650892.02	115V/60Hz (Nema N5-15 Plug) (R404A)		
9650892.03	230V/50-60Hz (Schuko Plug - CEE 7/4 Plug Type F) (R404A)		
9650892.04	230V/50-60Hz (UK Plug Type BS1363A) (R404A)		
9650892.05	230V/50-60Hz (CH Plug Type SEV 1011) (R404A)		

Dimensions probe tube cm (L x 🛚)



Other		Electronics		
IP Code	IP 21	External pt100 sensor connection	integrated	
		Temperature control	PID1	
		Temperature display	LED	
		Temperature setting	Keypad	
Immersion cooler		Dimensions and volumes		
Dimensions probe tube Length cm (L x ⋈) 64		Weight kg	50	
Dimensions probe tube Diameter cm	1.5	Dimensions cm (W × L × H)	38 x 55 x 60	
Immersion probe type	flexible			

Temperature values	
Working temperature range °C	-90 + 30
Temperature stability °C	±1
Ambient temperature °C	+5 +35
Temperature display resolution °C	0.1

64 x 1.5

All Benefits



100% Checked.

100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Green technology.

Development consistently applied environmentally friendly materials and technologies.



JULABO. Quality.

Highest standards of quality for a long product life.



Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.