

DAIHAN-brand® 1,200°C Programmable Digital Muffle Furnaces “FHX”, Exposed Heating Elements-type with Digital PID Control, Short Heat-up Time, Ceramic Fiber, 4-Side Heating, with Ceramic Fiber Plate, 3~63 Lit 디지털 전기로, 디지털 PID 컨트롤 시스템, 4면 가열 방식, 히터 노출형



Jog-Shuttle with Push Button

2-Year Warranty

1200°C Digital Muffle Furnace, Exposed Heating Elements-type “FHX-14”

- Made in Korea ■ CE Certified ■ PL (Product Liability) Insurance
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Patented Jog-Dial Control System and Digital LCD with Back-Light Function
- Digital PID Programmable Controller : 4 Patterns with 10 Segments

- * Digital Jog-Dial Control System
- * Ceramic Fiber Exposed Heating Wire, 4-Side Heating
- * User's Self-Compensation Function for Temperature (± 50°C)
- * Included Ceramic Fiber Plate
- * Safety Switch for Door Opening
- * Resolution : 1°C, 1min

Specifications & Ordering information

Spec.	Model	“FHX-03”	“FHX-05”	“FHX-12”	“FHX-14”	“FHX-27”	“FHX-63”
Temp. Range		300°C ~ 1200°C					
Capacity		3 Lit.	4.5 Lit.	12 Lit.	14 Lit.	27 Lit.	63 Lit.
Heater		Kanthal A1, Expose Wire Heating Elements, 4-Side Heating					
Thermocouple		K-type Thermocouple					
Heating Power		1.6 kW	1.7 kW	3.3 kW	4.0 kW	4.6 kW	9 kW
Required time to be reached 800°C		16 min		20 min		23 min	
Timer & Alarm		99hr 59min (Continuous run), Error status & Timer-end					
Display		Digital LCD with Back-Light Function					
Controller		Digital PID Controller with Jog-Dial Switch (Turn+Push)					
Program Function		4 Patterns with 10 Segments					
Safety Circuit		Over-Temp./-Current protection, Sensor Error Detection Safety Switch for Door Opening					
Material		Ceramic Fiber with Heating Wire-Internal, Powder Coated steel-External Ceramic Fiber-Insulation					
Dimension (w×d×h)	Internal (cm)	13×25×9	15×30×10	20×30×20	25×35×16	30×30×30	40×40×40
	External (cm)	41×48×53	44×53×55	50×55×66	55×59×62	60×59×76	100×75×95
Packing Size(w×d×h) (cm)		63×54×77	68×57×78	70×63×89	74×68×85	74×73×99	116×90×110
Gross Weight		47 kg	54 kg	59 kg	73 kg	83 kg	225 kg
Electrical Reqt.s.		1 Phase, AC 120V, 60Hz or AC 230V, 50/60Hz		1 Phase AC 120V, 60Hz or AC 230V, 50/60Hz or 3 Phase			
Cat. No.	230V	DH.WFH22.03	DH.WFH22.05	DH.WFH22.12	DH.WFH22.14	DH.WFH22.27	DH.WFH22.63
	120V	DH.WFH20.03	DH.WFH20.05	DH.WFH20.12	DH.WFH20.14	DH.WFH20.27	DH.WFH20.63
	3Phase	-	-	DH.WFH23.12	DH.WFH23.14	DH.WFH23.27	DH.WFH23.63
Price, Each. ₩							

* Other Specifications are available upon Customer's Request.

※ 운임 약 ₩ 20,000 별도!



2-Year Warranty

1200°C Digital Muffle Furnace, Exposed Heating Elements-type “FHX-63”

Spare Ceramic Fiber Plates

- DH.WF211.03 (1) Ceramic Fiber Plate, 120×215mm, “FS1103” for 3Lit.
- DH.WF211.05 , 140×265mm, “FS1105” for 4.5Lit.
- DH.WF211.12 , 190×265mm, “FS1112” for 12Lit.
- DH.WF211.14 , 240×310mm, “FS1114” for 14Lit.
- DH.WF211.27 , 280×280mm, “FS1127” for 27Lit.
- DH.WF211.63 , 400×400mm, “FS1163” for 63Lit.

Ea. Price, ₩

Optional Gloves

- AS1.7896.01 (2) Gloves, Heat Resistant, 1000°C, 1Pair, L450 mm
- AS1.7896.02 , L350 mm

Ea. Price, ₩



Inner Chamber of Exposed Heating Elements-type



(1) Ceramic Fiber Plate (Included)



(2) Heat-resistant Gloves