

DAIHAN-brand® Aluminum-case Beaker Heating Mantles, (1) Basic & (2) Stirring-type, 450°C, 100~5,000ml with Built-in Temp Controller, with/without Mag-stir Speed Control, with Certi. & Traceability
 비이커용 히팅맨틀, 온도 조절기 내장, “기본형” 및 “자석교반형”, Ni-Cr열선 내장

- Made in Korea
- Ideal for All type Beakers
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Built-in Temp-Controller. Nickel-Chrome Heating Element “Coil-type” : Acid Resistant & Long Life Time.



(1) Basic-type Beaker Mantle with Controller

(1) Basic-type Beaker Mantles, Built-in Temp. Controller

* With a Device* for Holding a Optional Stainless-steel Rod ϕ 12.7 mm for Article Support.

Beakers, ml Dia. ϕ mm	Mantle			Catalog No.		Ea. Price, ₩
	Watts (W)	Inside Depth	Outside $\phi \times H$ (mm)	with 230V	with 120V	
100ml, ϕ 50~52	80 W	40 mm	ϕ 145 \times H140	DH.WHM12141	DH.WHM12151	
250ml, ϕ 68~70	140 W	65 mm	ϕ 145 \times H140	DH.WHM12142	DH.WHM12152	
400ml, ϕ 79~81	240 W	70 mm	ϕ 145 \times H140	DH.WHM12143	DH.WHM12153	
600ml, ϕ 88~90	240 W	75 mm	ϕ 145 \times H140	DH.WHM12144	DH.WHM12154	
800ml, ϕ 98~100	300 W	90 mm	ϕ 190 \times H165	DH.WHM12145	DH.WHM12155	
1,000ml, ϕ 105~108	350 W	90 mm	ϕ 190 \times H165	DH.WHM12146	DH.WHM12156	
2,000ml, ϕ 130~132	450 W	125 mm	ϕ 199 \times H190	DH.WHM12147	DH.WHM12157	
3,000ml, ϕ 151~153	550 W	160 mm	ϕ 270 \times H235	DH.WHM12148	DH.WHM12158	
4,000ml, ϕ 160~162	700 W	160 mm	ϕ 270 \times H235	DH.WHM121481	DH.WHM121581	
5,000ml, ϕ 169~171	800 W	160 mm	ϕ 270 \times H235	DH.WHM12149	DH.WHM12159	




(2) Stirring-type Beaker Mantle with a Stir-Bar

(2) Stirring-type Beaker Mantles, Built-in 50~75rpm Mag-stir Speed & Temp. Controller

* With a Device* for Holding a Optional Stainless-steel Rod ϕ 12.7 mm for Article Support.

* With 1ea \times PTFE Octagonal Magnetic Stirrer Bar, L38mm

Beakers, ml Dia. ϕ mm	Mantle			Catalog No.		Ea. Price, ₩
	Watts (W)	Inside Depth	Outside $\phi \times H$ (mm)	with 230V	with 120V	
100ml, ϕ 50~52	80 W	45 mm	ϕ 145 \times H140	DH.WHM121601	DH.WHM121611	
250ml, ϕ 68~70	140 W	70 mm	ϕ 190 \times H165	DH.WHM121602	DH.WHM121612	
400ml, ϕ 79~81	240 W	70 mm	ϕ 190 \times H165	DH.WHM121603	DH.WHM121613	
600ml, ϕ 88~90	240 W	72 mm	ϕ 190 \times H165	DH.WHM121605	DH.WHM121615	
1,000ml, ϕ 105~108	350 W	105 mm	ϕ 190 \times H190	DH.WHM121606	DH.WHM121616	
2,000ml, ϕ 130~132	450 W	140 mm	ϕ 270 \times H235	DH.WHM121607	DH.WHM121617	
3,000ml, ϕ 151~153	550 W	140 mm	ϕ 270 \times H235	DH.WHM121608	DH.WHM121618	
4,000ml, ϕ 160~162	700 W	170 mm	ϕ 325 \times H270	DH.WHM121609	DH.WHM121619	
5,000ml, ϕ 169~171	800 W	170 mm	ϕ 325 \times H270	DH.WHM121610	DH.WHM121620	



(3) Stand Rod, “RD300”, ϕ 12.7 \times L520mm

(4) Holder / Clamp / Clip for Temp. Probe

Optional Stainless-steel Rod, Holder & Clamp

DH.WHP503037 (3) Stand Rod, ϕ 12.7 \times L520mm, “RD300”, for Heating Mantles

DH.WHP503012 (4) Holder & Clamp, “CL220”, for Temp. Sensor

Ea. Price, ₩