


DAIHAN-brand® 380°C Analog Premium Hotplate “HP-20A” & “HP-30A”, Ceramic-Coated Plate  
 Built-in Linearity PWM Controller, High Temp. Uniformity, 180×180- or 260×260-mm Plate, CE Certified, with Certi. & Traceability  
 아날로그 정밀 가열판, 우수한 온도균일성 & 경제성, 세라믹 코팅 플레이트



(a) 180×180mm Plate-type Hotplate “HP-20A”



(b) 260×260mm Plate-type Hotplate “HP-30A”


- Made in Korea
- CE Certified
- PL (Product Liability) Insurance
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Excellent for Sample Drying and Most General Lab Heating Applications
- Superior Temperature Uniformity : Less than 10% on the Plate at Ambient Temperature

- \* Excellent for Sample Drying and most General lab Heating Applications
- \* Smart Design of Body made by Aluminum Die-Casting (HP-20A)
- \* Superior Temperature Uniformity : Less than 10% on the Plate at Ambient Temperature
- \* Superior Linearity for Temperature Control by Specially Designed Control Circuitry (PWM control)
- \* Ceramic Coated Plate - Chemical / Acid Resistance

### Specifications & Ordering information

Spec.	Model	(a) “HP-20A”	(b) “HP-30A”
Plate Size(mm)		180×180mm Plate-type	260×260mm Plate-type
Material	Body	Powder Coated Aluminum	Powder Coated steel
	Plate	Ceramic Coated Aluminum (Chemical / Acid Resistance, Easy to Clean)	
Temp. Range & Uniformity		Max. 380°C Temp., High Uniformity : Difference 10% less	
Heating Power/Consumption		600 W	1.2 kW
Controller		Superior Linearity PWM Controller	
Permissible Temp. & RH %		R/T +5 ~ 50°C, 85% RH	
Dimension & Weight		206×307×h99mm, 2.8kg	286×387×h99mm, 3.3kg
Packing Size & Gross Weight		400×280×h200mm, 5 kg	430×320×200hmm, 5 kg
Electrical Rqts.		1 Phase, AC 120 V, 60 Hz or AC 230 V, 50 / 60 Hz	
Cat. No.	230V	DH.WHP03120	DH.WHP03121
	120V	DH.WHP02120	DH.WHP02121
Price, Each. ₩			

\* Other Specifications are available upon Customer's Request.



### Optional Stand Rod & Holder/Clamp

- DH.WHP503011 (1) Stand Rod, “RD100”, Stainless steel, Non-screw  $\phi 12.7 \times L390\text{mm}$ , for “HP-30A/30D”, “MSH-30A/30D”
- DH.WHP503036 (2) Stand Rod, “RD200”, Stainless steel, 1.5p screw  $\phi 12 \times L450\text{mm}$ , for “HP-20A/20D”, “MSH-20A/20D”, “MSH-50A/55A”, “MSH-50D/55D” and “SMHS”
- DH.WHP503012 (3) Holder / Clamp / Clip, “CL220”, for Temp. Probe

Ea. Price, ₩

### Specialized Features

