

1248 · 1248R · 1236R · 1580 · 1580R

Swing-out Rotor,
GRS-G-100-6

6 loadings
∠ 90°



Round 100 ml Bucket with Cap
GLB-b100-100

Bucket bore (Φ x L, mm) : 47 x 99
Radius (mm) : 173.6
Max.RPM : 4,000
Max.RCF (g-force) : 3,105
Max.height for tube fit (mm)
: 120(w/ cap) / 130(w/o cap)

* GLB-b100-100 includes cap.
* (b100) adaptors work fine with cap but (100) adaptors not.

Tube										
Tube capacity (ml)	1.5~2.0	2.6~7	4~10	9~15	15 ml conical	15 ml conical	50 ml	50 ml conical	85	100
Tube rack										
Cat. No.	GAM-m2.0-6 (b100)	GAM-7-5 (b100)	GAM-10-5 (b100)	GAM-15-3 (100)	GAM-c15-3 (100)	GAS-c15 (b100)	GAS-50 (b100)	GAS-c50 (b100)	GAS-85 (b100)	GAS-100 (b100)
Rack capacity (ea/6)	6/36	5/30	5/30	3/18	3/18	1/6	1/6	1/6	1/6	1/6
Hole dimension (Φ x L, mm)	11 x 39	13.5 x 60	16 x 60	17.5 x 105	17.2 x 106.5	17.2 x 106.5	29.5 x 95.9	30 x 100	38.5 x 96.4	44.2 x 93