

Swing-out Rotor, GRS-L-750-6

6 loadings
 $\leq 90^\circ$



Round 750 ml Bucket GLB-750-750

Bucket bore (Φ x L, mm) : 99 x 101.5
 Radius (mm) : 222.6
 Max.RPM : 4,000
 Max.RCF(g-force) : 3,982
 Max.height for tube fit (mm) : 142

Tube											
Tube capacity (ml)	3	5	10	15	15 ml conical	50	50 ml conical	250	250 ml conical	500 ml conical	750
Tube rack											None
Cat. No.	GAM-5-24(750)		GAM-10-21(750)	GAM-15-19(750)	GAM-c15-14(750)	GAM-50-7(750)	GAM-c50-5(750)	GAS-250(750)	GAS-c250(750)	GAS-c500(750)	-
Rack capacity (ea/6)	24/144		21/126	19/114	14/84	7/42	5/30	1/6	1/6	1/6	1/6
Hole dimension (Φ x L, mm)	13.2 x 58	13.2 x 85	16 x 85	17.2 x 85	17 x 85	29.2 x 87	29.2 x 88	62.3 x 87	60.5 x 125	95.6 x 58	-



Round 500ml Bucket GLB-500-750

Bucket bore (Φ x L, mm) : 69.2 x 135
 Radius (mm) : 237.5
 Max.RPM : 4,000
 Max.RCF(g-force) : 4,248
 Max.height for tube fit (mm) : 165

Tube	
Tube capacity (ml)	500
Bucket capacity (ea/6)	1/6



Microplate Holder GLP-mw-750

Holder bore (w x d x h, mm)
 : 88 x 128.5 x 80
 Radius (mm) : 189.2
 Max.RPM : 4,000
 Max.RCF (g-force) : 3,384

Plate		
Plate capacity (ml)	MTP	DWP
Holder capacity (ea/6)	4/24	1/6