






Fixed Angle Rotor, GRF-L-500-6



6 x 500 ml
 \angle 25°
 Hole diameter (mm) : 70
 Max. height for tube fit (mm) : 170

| | | |
|------------------------|---|---|
| Tube |  |  |
| Tube capacity (ml) | 250 | 500 |
| Adaptor |  | None |
| Cat No. | GAS-250(500) | - |
| Adaptor bore (ΦxL, mm) | 69 x 100 | - |
| Radius (mm) | 138.3 | 158 |
| Max.RPM | 8,000 | |
| Max.RCF (g-force) | 9,896 | 11,305 |



Fixed Angle Rotor, GRF-L-250-6












6 x 250 ml (6 x 15 ml)
 \angle 25°
 Hole diameter (250/15) (mm) : 62/17
 Max. height for tube fit (250/15) (mm)
 : 130/120

| | | |
|--------------------|---|---|
| Tube |  |  |
| Tube capacity (ml) | 15 | 250 |
| Radius (mm) | 131.3 | 134 |
| Max.RPM | 10,000 | |
| Max.RCF (g-force) | 14,679 | 14,981 |



Fixed Angle Rotor, GRF-L-85-6

6 x 85 ml
 \angle 25°
 Hole diameter (mm) : 38.3
 Max. height for tube fit (mm) : 125

| | | | | | | |
|------------------------|---|---|---|---|---|---|
| Tube |  |  |  |  |  |  |
| Tube capacity (ml) | 10 | 15 | 15 ml conical | 50 | 50 ml conical | 85 |
| Adaptor |  |  |  |  |  | None |
| Cat. No. | GAS-15(85) | GAS-c15(85) | GAS-50(85) | GAS-c50(85) | - | |
| Adaptor bore (ΦxL, mm) | 17 x 94 | | 17 x 98 | 29 x 95 | 29.5 x 98 | |
| Radius (mm) | 91.5 | 92.5 | 90.5 | 93.5 | 91.5 | 99.5 |
| Max.RPM | 15,000 | | | | | |
| Max.RCF (g-force) | 23,017 | 23,268 | 22,765 | 23,520 | 23,017 | 25,029 |