






## Fixed Angle Rotor, GRF-L-500-6



6 x 500 ml  
 $\angle 25^\circ$   
 Hole diameter (mm) : 70  
 Max. height for tube fit (mm) : 170

Tube		
Tube capacity (ml)	250	500
Adaptor		None
Cat No.	<b>GAS-250(500)</b>	-
Adaptor bore ( $\Phi \times L$ , mm)	69 x 100	-
Radius (mm)	138.3	158
Max.RPM	10,000	
Max.RCF (g-force)	15,462	17,664



## Fixed Angle Rotor, GRF-L-250-6











6 x 250 ml (6 x 15ml)  
 $\angle 25^\circ$   
 Hole diameter (250/15) (mm) : 62/17  
 Max. height for tube fit (250/15) (mm) : 130/120

Tube		
Tube capacity (ml)	15	250
Radius (mm)	131.3	134
Max.RPM	13,000	
Max.RCF (g-force)	24,808	25,318



## Fixed Angle Rotor, GRF-L-85-6

6 x 85 ml  
 $\angle 25^\circ$   
 Hole diameter (mm) : 38.3  
 Max. height for tube fit (mm) : 125

Tube						
Tube capacity (ml)	10	15	15ml conical	50	50ml conical	85
Adaptor						None
Cat. No.	<b>GAS-15(85)</b>		<b>GAS-c15(85)</b>	<b>GAS-50(85)</b>	<b>GAS-c50(85)</b>	-
Adaptor bore ( $\Phi \times L$ , mm)	17 x 94		17 x 98	29 x 95	29.5 x 98	-
Radius (mm)	91.5	92.5	90.5	93.5	91.5	99.5
Max.RPM	20,000					
Max.RCF (g-force)	40,919	41,366	40,472	41,813	40,919	44,496