



1248 · 1248R · 1236R · 1580 · 1580R



Fixed Angle Rotor, GRF-G-250-6

6 x (250 & 15 ml)
 \angle 25°
 Hole diameter (250/15) (mm) : 62/17
 Max height for tube fit (250/15) (mm) :
 130/120











Only for 1580R

Tube		
Tube capacity (ml)	15	250
Radius (mm)	131.3	134
Max.RPM (1580R)	8,000	
Max.RCF (g-force)	9,395	9,588



Fixed Angle Rotor, GRF-G-85-6

6 x 85 ml
 \angle 34°
 Hole diameter (mm) : 38.5
 Max. height for tube fit (mm) : 122

Tube						
Tube capacity (ml)	10	15	15 ml conical	50	50 ml conical	85
Adaptor						None
Cat. No.	GAS-15(85)		GAS-c15(85)	GAS-50(85)	GAS-c50(85)	-
Adaptor bore (ΦxL, mm)	17 x 94		17 x 98	29 x 95	29.5 x 98	-
Radius (mm)	102	103	101	104	102	110
Max.RPM (1580R)	12,000					
Max.RCF (g-force)	16,424	16,582	16,260	16,743	16,421	17,709
Max.RPM (1248/1248R/1236R/1580)	10,000					
Max.RCF (g-force)	11,404	11,515	11,292	11,627	11,404	12,298