

Swing-out Rotor, GRS-S-50-4

4 loadings
 $\leq 90^\circ$



Round 50 ml Bucket
GLB-50-50

Bucket bore ($\Phi \times L$, mm) : 30.5 x 91
 Radius(mm) : 150.9
 Max.RPM : 4,000
 Max.RCF(g-force) : 2,700
 Max.height for tube fit(mm) : 125

Tube				
Tube capacity (ml)	15	15 ml conical	50 ml conical	50
Adaptor				None
Cat. No.	GAS-u15(50)	GAS-c50(50)		-
Adaptor bore ($\Phi \times L$, mm)	17.3 x 87	29.5 x 17.5		-



Conical 50 ml Bucket
GLB-c50-50

Bucket bore ($\Phi \times L$, mm) : 29.5 x 91.5
 Radius(mm) : 150.9
 Max.RPM : 4,000
 Max.RCF(g-force) : 2,700
 Max.height for tube fit(mm) : 125

Tube	
Tube capacity (ml)	50 ml conical



Round 15 ml Bucket
GLB-15-50

Bucket bore ($\Phi \times L$, mm) : 17 x 93
 Radius(mm) : 150.9
 Max.RPM : 4,000
 Max.RCF(g-force) : 2,700
 Max.height for tube fit(mm) : 125

Tube	
Tube capacity (ml)	15



Conical 15 ml Bucket
GLB-c15-50

Bucket bore ($\Phi \times L$, mm) : 17 x 93
 Radius(mm) : 150.9
 Max.RPM : 4,000
 Max.RCF(g-force) : 2,700
 Max.height for tube fit(mm) : 120

Tube	
Tube capacity(ml)	15 ml conical



Dual Round 15 ml Bucket
GLB-d15-50

Bucket bore ($\Phi \times L$, mm) : 17 x 91.5
 Radius(mm) : 150.9
 Max.RPM : 4,000
 Max.RCF(g-force) : 2,700
 Max.height for tube fit(mm) : 120

Tube	
Tube capacity (ml)	15
Bucket capacity (ea/4)	2/8



Dual Conical 15 ml Bucket
GLB-dc15-50

Bucket bore ($\Phi \times L$, mm) : 17 x 91.5
 Radius(mm) : 150.9
 Max.RPM : 4,000
 Max.RCF(g-force) : 2,700
 Max.height for tube fit(mm) : 120

Tube	
Tube capacity (ml)	15 ml conical
Bucket capacity (ea/4)	2/8