

Swing-out Rotor, GRS-SR-50-4

4 loadings
∠ 90°



Round 50 ml Bucket
GLB-50-50

Bucket bore(Φ x L, mm)
: 30.5 x 91
Radius(mm) : 150.9
Max.RPM : 4,800
Max.RCF(g-force) : 3,888
Max.height for tube fit(mm) : 125

Tube				
Tube capacity (ml)	15	15 ml conical	50 ml conical	50
Adaptor			None	
Cat. No.	GAS-u15(50)	GAS-c50(50)	-	
Adaptor bore (Φ x L, mm)	17.3 x 87	29.5 x 17.5	-	



Conical 50 ml Bucket
GLB-c50-50

Bucket bore(Φ x L, mm)
: 29.5 x 91.5
Radius(mm) : 150.9
Max.RPM : 4,800
Max.RCF(g-force) : 3,888
Max.height for tube fit(mm) : 125

Tube	
Tube capacity (ml)	50 ml conical



Round 15 ml Bucket
GLB-15-50

Bucket bore(Φ x L, mm)
: 17 x 93
Radius(mm) : 150.9
Max.RPM : 4,800
Max.RCF(g-force) : 3,888
Max.height for tube fit(mm) : 125

Tube	
Tube capacity (ml)	15



Conical 15 ml Bucket
GLB-c15-50

Bucket bore(Φ x L, mm)
: 17 x 93
Radius(mm) : 150.9
Max.RPM : 4,800
Max.RCF(g-force) : 3,888
Max.height for tube fit(mm)
: 120

Tube	
Tube capacity(ml)	15 ml conical



Dual Round 15 ml Bucket
GLB-d15-50

Bucket bore(Φ x L, mm)
: 17 x 91.5
Radius(mm) : 150.9
Max.RPM : 4,800
Max.RCF(g-force) : 3,888
Max.height for tube fit(mm) : 120

Tube	
Tube capacity (ml)	15
Bucket capacity (ea/4)	2/8



Dual Conical 15 ml Bucket
GLB-dc15-50

Bucket bore(Φ x L, mm)
: 17 x 91.5
Radius(mm) : 150.9
Max.RPM : 4,800
Max.RCF(g-force) : 3,888
Max.height for tube fit(mm) : 120

Tube	
Tube capacity (ml)	15 ml conical
Bucket capacity (ea/4)	2/8