





15 mL Dual Round Bucket
with a Cap
GLB-bd15-100

Max. RPM / RCF : 4,000 / 3,032
Max. Radius (mm) : 169.5
Hole dimension (Ø x L, mm) : 17 x 87
Max. height for tube fit (mm) : 115 (w/ cap) / 127 (w/o cap)
Hole bottom type : Round
Supplied with a cap and O-ring








| Tube |  |  |  |
|----------------------------|---|---|---|
| Tube capacity (mL) | 15 mL glass | 15 mL open top | 15 |
| Tube Dimension (Φ x L, mm) | 16 x 100 | 16 x 114 | 16 x 120 |
| Bucket capacity (ea / 6) | 2 / 12 | 2 / 12 | 2 / 12 |
| Max. height tube fit (mm) | 115 | 115 | 115 |
| Max. radius (mm) | 169.5 | 169.5 | 169.5 |
| Max. RCF (g-force) | 3,032 | 3,032 | 3,032 |

Bio-Safe Porton Down Certified



15 mL Dual Conical Bucket
with a Cap
GLBB-bdc15-100

Max. RPM / RCF : 4,000 / 3,105
Max. Radius (mm) : 173.6
Hole dimension (Ø x L, mm) : 17 x 97.5
Max. height for tube fit (mm) : 120 (w/ cap) / 125 (w/o cap)
Hole bottom type : Conical
Supplied with a cap and O-ring, No cap version is available

| Tube |  |  |  |  |
|------------------------------------|---|---|---|---|
| Tube capacity (mL) | 5 mL conical | 5 mL conical | 14 mL | 15 mL conical |
| Tube Dimension (Φ x L, mm) | 16 x 59 | 16 x 67 | 15.7 x 96 | 17 x 120 |
| Adapter |  |  |  | None |
| Cat No. | GAS-c5(c15) | GAS-c5(c15) | GAS-14(c15) | - |
| Bucket capacity (ea / 6) | 2 / 12 | 2 / 12 | 2 / 12 | 2 / 12 |
| Adaptor hole dimension (Φ x L, mm) | 14.8 x 20 | 14.8 x 20 | 16 x 7.8 | - |
| Adaptor hole bottom type | Conical | Conical | Round | - |
| Max. radius (mm) | 120.5 | 120.5 | 156.5 | 173.6 |
| Max. RCF (g-force) | 2,156 | 2,156 | 2,799 | 3,105 |