


# Angle Rotor, GRA-15/10-12A, GRA-15-6A

- Capacity : 6 x 15 mL or 12 x 10 mL / 6 X 15 mL
- Max. RPM / RCF : 4,000 / 2,075
- Hole angle rotation :  $\angle 45^\circ$
- Hole dimension ( $\varnothing \times L$ , mm) : 20.4 x 10.1
- Supplied with 12 sleeves, No ID ring



15 mL Sleeve  
**GLB-15/10A**

Max. Capacity : 15 mL  
 Max RPM / RCF : 4,000 / 2,075  
 Hole dimension ( $\varnothing \times L$ , mm) : 18 x 87  
 Hole bottom type : Flat bottom with rubber pad  
 Supplied with 4.0 mm thick NBR pad inserted

Tube								
Tube capacity (mL)	2.0 ~ 4 mL VT	4 ~ 7 mL VT	5 mL conical	5 mL conical	14 mL	8 ~ 10 mL VT	15	15 mL conical
Tube Dimension ( $\varnothing \times L$ , mm)	13 x 75	13 x 100	16 x 59	16 x 67	15.7 x 96	16 x 100	16 x 120	17 x 120
Adapter						None	None	None
Cat No.	GAS-3(f15)	GAS-5(f15)	GAS-c5(f15)	GAS-c5(f15)	GAS-14(f15)	-	-	-
Adaptor hole dimension ( $\varnothing \times L$ , mm)	13.5 x 61	13.5 x 85	14 x 20	14 x 20	16.5 x 7	-	-	-
Adaptor hole bottom type	Round	Open	Conical	Conical	Round	-	-	-
Max. radius (mm)*	95.5	111	81.5	81.5	104.5	116	116	116
Max. RCF (g-force)*	1,708	1,986	1,458	1,458	1,869	2,075	2,075	2,075

