

Angle Rotor, GRA-S-15-16A

16 x 15 ml
 ∠ 45°
 Hole diameter (mm) : 18
 Max. height for tube fit (mm) :
 120 for conical tube



Swing-Out Rotor, GRS-S-15-6

6 loadings
 ∠ 90°



Aluminum 15ml Sleeve
GLB-15A-FA
 Sleeve bore (Φ x L, mm) : 18 x 90
 Radius (mm) : 151.5
 Max. RPM : 4,000
 Max. RCF (g-force) : 2,700

Tube						
Tube capacity (ml)	3	4	5	10	15	15ml conical
Adaptor				None	None	None
Cat. No.	GAS-3(15)	GAS-4(15)	GAS-5(15)	-	-	-
Adaptor bore (Φ x L, mm)	13.5 x 61	13.5 x 65	13.5 x 85	-	-	-
Radius (mm)	134	136	146	150.5	150.9	147.5
Max. RPM	4,000					
Max. RCF (g-force)	2,397	2,433	2,612	2,692	2,700	2,638



Round 15ml Bucket
GLB-15-15
 Bucket bore(Φ x L):17 x 93.8
 Radius(mm):158
 Max.RPM:4,000
 Max.RCF(g-force):2,826
 Max.height for tube fit(mm):125

Tube		
Tube capacity (ml)	10	15

Swing-Out Rotor, GRS-S-mw-2

2 loadings
 ∠ 90°
 Area dimension (mm) : 88.5 x 130.3
 Max. height for microplate fit (mm) : 35



Plate		
Plate capacity (ml)	MTP	DWP
Holder capacity (ea/2)	1/2	
Radius (mm)	111	
Max. RPM	4,000	
Max. RCF (g-force)	1,986	