



### Fixed Angle Rotor, GRE-M-m2.0-24

24 x 1.5/2.0 ml  
 $\angle 45^\circ$   
 Hole diameter (mm) : 11.1  
 Max. height for tube fit (mm) : 52

Tube			
Tube capacity (ml)	0.2	0.5	1.5/2.0
Adaptor			None
Cat No.	GAS-m0.2(2)	GAS-m0.5(2)	-
Adaptor bore ( $\Phi \times L$ , mm)	6.5 x 23	8 x 31	-
Radius (mm)	67	73	84.3
Max.RPM	17,000		
Max.RCF (g-force)	21,648	23,910	27,237



### Fixed Angle Rotor, GRE-M-m2.0-30

30 x 1.5/2.0 ml  
 $\angle 45^\circ$   
 Hole diameter (mm) : 11.1  
 Max. height for tube fit (mm) : 52

Tube			
Tube capacity (ml)	0.2	0.5	1.5/2.0
Adaptor			None
Cat No.	GAS-m0.2(2)	GAS-m0.5(2)	-
Adaptor bore ( $\Phi \times L$ , mm)	6.5 x 23	8 x 31	-
Radius (mm)	79	86	96.4
Max.RPM	14,000		
Max.RCF (g-force)	17,311	18,845	21,124



### Fixed Angle Rotor, GRE-M-m2.0-18

18 x 1.5/2.0 ml  
 $\angle 45^\circ$   
 Hole diameter (mm) : 11.1  
 Max. height for tube fit (mm) : 65

Tube				
Tube capacity (ml)	0.2	0.5	1.5/2.0	2 ml filter tube
Adaptor			None	None
Cat No.	GAS-m0.2(2)	GAS-m0.5(2)	-	-
Adaptor bore ( $\Phi \times L$ , mm)	6.5 x 23	8 x 31	-	-
Radius (mm)	57.8	63.8	75.1	64.2
Max.RPM	15,000			
Max.RCF (g-force)	14,540	16,049	18,891	16,150