



## Fixed Angle Rotor, GRE-M-m5.0-12

- Capacity : 12 x 5.0 mL
- Max. RPM / RCF : 15,000 / 22,967
- Hole angle from axis during rotation :  $\angle 45^\circ$
- Hole dimension ( $\varnothing \times L$ ,mm) : 17 x 53
- Hole bottom type : Conical
- Max. height for tube fit (mm) : 68
- Supplied with a lid and two V-rings inserted











Tube		
Tube capacity (mL)	5.0	5.0
Tube Dimension ( $\Phi \times L$ ,mm)	16 x 59	16 x 67
Max. radius (mm)	91.3	91.3
Max. RCF (g-force)	22,967	22,967

## Fixed Angle Rotor, GRE-M-m2.0-36

- Capacity : 36 x 1.5/2.0 mL (24 outer, 12 inner) plus 12 x 0.2 mL(inner)
- Max. RPM / RCF : 15,000 / 21,206
- Hole angle from axis during rotation :  $\angle 45^\circ$
- Hole dimension ( $\varnothing \times L$ ,mm) : 11.1 x 39
- Hole bottom type : Round
- Max. height for tube fit (mm) : 52
- Supplied with a lid and two V-rings inserted



Tube						
Tube capacity (mL)	0.2	0.2	0.5	1.5/2.0	2.0 mL filter tube	2.0 mL screw cap
Tube Dimension ( $\Phi \times L$ , mm)	6 x 8	6 x 8	8 x 30	11 x 38	11 x 38	10.1 x 46
Adapter	None			None	None	None
Cat No.	-	GAS-m0.2(2)	GAS-m0.5(2)	-	-	-
Adaptor hole dimension ( $\Phi \times L$ ,mm)	-	6.5 x 23	8 x 31	-	-	-
Adaptor hole bottom type	-	Open	Open	-	-	-
Max. radius (mm)*	Inner 58.2	Inner 53.5 Outer 67	Inner 60.5 Outer 73	Inner 70.9 Outer 84.3	70.9	Inner 70.9 Outer 84.3
Max. RCF (g-force)*	Inner 14,640	Inner 13,458 Outer 16,854	Inner 15,219 Outer 18,363	Inner 17,835 Outer 21,206	17,835	Inner 17,835 Outer 21,206