

# 1536



## Fixed Angle Rotor, GRE-m2.0-24

24 x 1.5/2.0 ml  
 $\angle 45^\circ$   
 Hole diameter (mm) : 11.1  
 Max. height for tube fit (mm) : 52

Tube			
Tube capacity (ml)	0.2	0.5	1.5/2.0
Adaptor			None
Cat No.	GAS-m0.2(2)	GAS-m0.5(2)	-
Adaptor bore ( $\Phi \times L$ , mm)	6.5 x 23	8 x 31	-
Radius (mm)	67	73	84.3
Max.RPM	15,000		
Max.RCF (g-force)	16,854	18,363	21,206



## Fixed Angle Rotor, GRE-m2.0-36

36 x 1.5/2.0 ml (12 x 0.2 ml)  
 $\angle 45^\circ$   
 Hole diameter (mm) : 11.1  
 Max. height for tube fit (mm) : 52

Tube					
Tube capacity (ml)	0.2	0.5	0.2	1.5/2.0	2 ml filter tube
Adaptor			None	None	None
Cat No.	GAS-m0.2(2)	GAS-m0.5(2)	-	-	-
Adaptor bore ( $\Phi \times L$ , mm)	6.5 x 23	8 x 31	-	-	-
Radius (mm)	53.5/67	60.5/73	58.2	70.9/84.3	59.1
Max.RPM	15,000				
Max.RCF (g-force)	13,458/16,854	15,219/18,363	14,640	17,835/21,206	14,867

\* It can accommodate only 12 x 2 ml filter tubes in the inner line.



## Fixed Angle Rotor, GRE-s0.2-32

8 x 8-Tube PCR strips, 32 x 0.2 ml  
 $\angle 45^\circ$   
 Hole diameter (mm) : 6.5  
 Max. height for tube fit (mm) : 16

Tube		
Tube capacity (ml)	0.2	8-Strip tube
Radius (mm)	56.4	
Max.RPM	15,000	
Max.RCF (g-force)	14,187	



## Fixed Angle Rotor, GRE-m5.0-10

10 x 5.0 ml  
 $\angle 45^\circ$   
 Hole diameter (mm) : 17  
 Max. height for tube fit (mm) : 68

Tube	
Tube capacity (ml)	5.0
Adaptor	None
Cat No.	-
Adaptor bore ( $\Phi \times L$ , mm)	-
Radius (mm)	85.8
Max.RPM	15,000
Max.RCF (g-force)	21,583