







Fixed Angle Rotor, GREB-m2.0-24

Bio-Safe

Porton Down Certified

- Capacity : 24 x 1.5/2.0 mL
- Max. RPM / RCF : 15,000 / 21,206
- Hole angle from axis during rotation : $\angle 45^\circ$
- Hole dimension ($\varnothing \times L$,mm) : 11.1 x 39
- Hole bottom type : Round
- Max. height for tube fit (mm) : 52
- Supplied with a lid and two V-rings inserted, No ID ring



| Tube |  |  |  |  |
|--|---|---|---|---|
| Tube capacity (mL) | 0.2 | 0.5 | 1.5/2.0 | 2.0 mL screw cap |
| Tube Dimension ($\varnothing \times L$, mm) | 6 x 8 | 8 x 30 | 11 x 38 | 10.1 x 46 |
| Adapter |  |  | None | None |
| Cat No. | GAS-m0.2(2) | GAS-m0.5(2) | - | - |
| Adaptor hole dimension ($\varnothing \times L$,mm) | 6.5 x 23 | 8 x 31 | - | - |
| Adaptor hole bottom type | Open | Open | - | - |
| Max. radius (mm)* | 67 | 73 | 84.3 | 84.3 |
| Max. RCF (g-force)* | 16,854 | 18,363 | 21,206 | 21,206 |



Fixed Angle Rotor, GREB-s0.2-32

Bio-Safe

Manufacturer Validated

- Capacity : 4 x 8-Tube PCR strips, 32 x 0.2 mL
- Max. RPM / RCF : 15,000 / 14,187
- Hole angle from axis during rotation : $\angle 45^\circ$
- Hole dimension ($\varnothing \times L$,mm) : 6.5 x 16
- Hole bottom type : Round
- Max. height for tube fit (mm) : 25
- Supplied with a lid and two V-rings inserted, No ID ring



| Tube |  |  |
|---|---|---|
| Tube capacity (mL) | 0.2 | 8-Strip tube |
| Tube dimension ($\varnothing \times L$, mm) | 6 x 8 | 6 x 8 |
| Max. radius (mm) | 56.4 | 56.4 |
| Max. RCF (g-force) | 14,187 | 14,187 |