

## Swing-out Rotor, GRS-SR-100-4

4 loadings  
 $\angle 90^\circ$



Round 100 ml Bucket  
with Cap

### GLB-b100-100

Bucket bore ( $\Phi$  x L, mm) : 47 x 99  
 Radius (mm) : 155.1  
 Max.RPM : 4,200  
 Max.RCF(g-force) : 3,059  
 Max.height for tube fit(mm)  
 : 120(w/ cap) / 130(w/o cap)

\* GLB-b100-100 includes cap. \* (b100) adaptors work fine with cap but (100) adaptors not.

Tube										
Tube capacity (ml)	1.5~2.0	2.6~7	4~10	9~15	15 ml conical	15 ml conical	50 ml	50 ml conical	85	100
Tube rack										
Cat. No.	GAM-m2.0-6 (b100)	GAM-7-5 (b100)	GAM-10-5 (b100)	GAM-15-3 (100)	GAM-c15-3 (100)	GAS-c15 (b100)	GAS-50 (b100)	GAS-c50 (b100)	GAS-85 (b100)	GAS-100 (b100)
Rack capacity (ea/4)	6/24	5/20	5/20	3/12	3/12	1/4	1/4	1/4	1/4	1/4
Hole dimension ( $\Phi$ xL, mm)	11 x 39	13.5 x 60	16 x 60	17.5 x 105	17.2 x 106.5	17.2 x 106.5	29.5 x 95.9	30 x 100	38.5 x 106.4	44.2 x 106.4