

Angle Rotor, GRV-8-60

- Capacity : 60 x 8 mL vial
- Max. RPM : 2,000
- Hole angle from axis during rotation : $\angle 50^\circ$
- Hole dimension (W x D x L,mm) : 18 x 25.5 x 2.5
- Hole bottom type : Open
- Max. height for tube fit (mm) : 70
- Min. height for tube fit (mm) : 52



Tube/Plate type



Tube capacity (mL)	8 mL vial
Tube Dimension (Φ x L,mm)	16.5 x 60.5

Angle Rotor, GRV-5-192

- Capacity : 192 x 5 mL
- Max. RPM : 2,000
- Hole angle from axis during rotation : $\angle 55^\circ$
- Hole dimension (W x D x L,mm) : 15.5 x 25 x 2.5
- Hole bottom type : Open
- Max. height for tube fit (mm) : 75
- Min. height for tube fit (mm) : 55



Tube/Plate type



Tube capacity (mL)	5 mL
Tube Dimension (Φ x L,mm)	11 x 66

Angle Rotor, GRV-mw-4

- 4 loadings
- Max. RPM : 2,000
- Angle from axis during rotation: $\angle 90^\circ$
- Rotor dimension / weight(Ø x L,mm / g) : 315 x 63.5 / 96.8



Microplate Bucket,
GLP-mw

Max. RPM : 2,000
Hole dimension (w x d ,mm) : 88.5 x 130.3
Max. height for tube fit (mm) : 35
Hole bottom type : Flat bottom

Tube/Plate type



Tube capacity (mL)	MTP	DWP
Tube Dimension (Φ x L,mm)	88 x 130x15	87 x 128 x 60
Bucket capacity(ea / 2)	2/4	1 / 4