



Cat. No	Description	Articles
---------	-------------	----------



Flexible Couplings, for Safety Stirring of $\phi 6\sim 16$ mm Shafts of Overhead Stirrers
 for Stirrers between Stirring Motor and Shaft, 안전교반용 유연성 커플링, 교반축의 불균형등을 완전 보정

■ **Used to Compensate Any Vibrations Between The Motor and Stirring Shafts** * Made of DURALUMIN
 * Made in Korea * Shaft Fastening by Screw Clamp Band * with Exchangeable STS Chucking Rod $\phi 8 / 10 / 12$ mm, L40mm



(1) Hi-flex Metal for $\phi 6\sim 16$ Shafts ; (2) Heavy-duty Metal for $\phi 10\sim 16$ Shafts

(1) UTILITY High-Flex. Metal Coupling, with 2 × Flex-band, for $\phi 6\sim 16$ mm Stir-Shafts
 Ideal for Low/High Viscosity and High/Low Speed

		Ea.	Price, ₩
SL.StiC011	Stir-Coupling, Hi-flex, $\phi 8$ mm Chuck-rod, for- $\phi 6$ mm Stir-Shaft, 56g, $\phi 25 \times h44$ mm		
SL.StiC012	- $\phi 8$ mm Stir-Shaft, 53g, $\phi 25 \times h44$ mm		
SL.StiC013	- $\phi 10$ mm Stir-Shaft, 49g, $\phi 25 \times h44$ mm		
SL.StiC014	Stir-Coupling, Hi-flex, $\phi 10$ mm Chuck-rod, for- $\phi 8$ mm Stir-Shaft, 49g, $\phi 25 \times h44$ mm		
SL.StiC015	- $\phi 10$ mm Stir-Shaft, 43g, $\phi 25 \times h44$ mm		
SL.StiC016	- $\phi 12$ mm Stir-Shaft, 33g, $\phi 25 \times h44$ mm		
SL.StiC017	Stir-Coupling, Hi-flex, $\phi 12$ mm Chuck-rod, for- $\phi 10$ mm Stir-Shaft, 33g, $\phi 25 \times h44$ mm		
SL.StiC018	- $\phi 12$ mm Stir-Shaft, 123g, $\phi 32 \times h60$ mm		
SL.StiC019	- $\phi 14$ mm Stir-Shaft, 120g, $\phi 32 \times h60$ mm		
SL.StiC020	- $\phi 16$ mm Stir-Shaft, 118g, $\phi 32 \times h60$ mm		

(2) Heavy-duty Metal Coupling, with Short Flex-band, for $\phi 10\sim 16$ mm Stir-Shafts
 Low-Flexible type, Ideal for High Viscosity and Middle/Low Speed

		Ea.	Price, ₩
SL.StiC023	Stir-Coupling, Low-flex, $\phi 10$ mm Chuck rod, for- $\phi 10$ mm Stir-Shafts., 45g, $\phi 25 \times h30$		
SL.StiC024	- $\phi 12$ mm Stir-Shafts., $\phi 25 \times h30$		
SL.StiC025	Stir-Coupling, Low-flex, $\phi 12$ mm Chuck rod, for- $\phi 12$ mm Stir-Shafts., 105g, $\phi 32 \times h38$		
SL.StiC026	- $\phi 14$ mm Stir-Shafts., $\phi 32 \times h38$		
SL.StiC027	- $\phi 16$ mm Stir-Shafts., $\phi 32 \times h38$		

SciLab-brand® PTFE Stirrer-Guide/Seals, for $\phi 8\sim \phi 14$ mm Shafts, with ₩24/-, ₩29/-, and ₩34/-Joints
 with 2 Bearings / Screw-Retainer / Viton O-ring, All PTFE, $-180\sim +260^\circ\text{C}$ Stable, PTFE 스티러 씰



■ **Made in Korea** ■ **Common-use : to ASTM & DIN-type Socket Joints**

(1) for $\phi 8$ mm Stir-Shafts

		Ea.	Price, ₩
SL.Ada405	for $\phi 8$ mm Rod, ₩24/40		
SL.Ada406	, ₩29/42		
SL.Ada407	, ₩34/45		

(2) for $\phi 10$ mm Stir-Shafts

		Ea.	Price, ₩
SL.Ada409	for $\phi 10$ mm Rod, ₩24/40		
SL.Ada410	, ₩29/42		
SL.Ada411	, ₩34/45		

(3) for $\phi 12$ & 14 mm Stir-Shafts

		Ea.	Price, ₩
SL.Ada413	PTFE Stir-Guide, for $\phi 12$ mm Rod, ₩34/45		
SL.Ada415	, for $\phi 14$ mm Rod, ₩34/45		

Multiuse Glass Screw-adapter Set, for Vacu-Stirrer Guide or Thermometer/Tubing Holder, for $\phi 6\sim 14$ mm-Grip
 with DURAN® PBT GL-Opentop Screwcap/PTFE-Silicone O-Ring Seal/ ₩Joint, Anti-Chemical, 200°C -stable, 다용도 스크류 어댑터 셋



(1) Vacuum Stirrer Guide
 (2) Thermometer/Tubing Holder

■ **Made of DURAN® Borosilicate Glass 3.3 & Seal Kit (GL-Opentop cap / O-Ring Seal : by SciLab Korea).**

(1) For Vacuum Stirrer Guide, for $\phi 8\sim 14$ mm Stir-Shafts, with DURAN® GL 25 & 32 Seal Kit & ₩Joint

① with ASTM ₩ 24/40 ~ 45/50 Joints

		Ea.	Price, ₩
SL.StiS241	for $\phi 8$ mm Rod, GL25, 24/40		
SL.StiS242	, 29/42		
SL.StiS243	, 34/45		
SL.StiS245	for $\phi 10$ mm Rod, GL25, 24/40		
SL.StiS246	, 29/42		
SL.StiS247	, GL32, 34/45		
SL.StiS251	for $\phi 12$ mm Rod, GL32, 34/45		
SL.StiS252	, 45/50		
SL.StiS253	for $\phi 14$ mm Rod, GL32, 34/45		
SL.StiS254	, 45/50		

② with DIN ₩ 24/29 ~ 45/40 Joints

		Ea.	Price, ₩
SL.StiS241D	for $\phi 8$ mm Rod, GL25, 24/29		
SL.StiS242D	, 29/32		
SL.StiS243D	, 34/35		
SL.StiS245D	for $\phi 10$ mm Rod, GL25, 24/29		
SL.StiS246D	, 29/32		
SL.StiS247D	, GL32, 34/35		
SL.StiS251D	for $\phi 12$ mm Rod, GL32, 34/35		
SL.StiS252D	, 45/40		
SL.StiS253D	for $\phi 14$ mm Rod, GL32, 34/35		
SL.StiS254D	, 45/40		

(2) For Thermometer/Tube/Rod Holder, for $\phi 6\sim 8$ mm Grip, with DURAN® GL14 & 18 Seal Kit & ₩Joint

① with ASTM & 14/23 Joints

		Ea.	Price, ₩
SL.Ada2011	for $\phi 6$ mm grip, GL14, 14/23		
SL.Ada2012	, 19/38		
SL.Ada2013	, 24/40		
SL.Ada2014	for $\phi 8$ mm grip, GL18, 24/40		

② with DIN ₩ Joints

		Ea.	Price, ₩
SL.Ada2011	for $\phi 6$ mm grip, GL14, 14/23		
SL.Ada2016	, 19/26		
SL.Ada2017	, 29/32		
SL.Ada2018	for $\phi 8$ mm grip, GL18, 29/32		