

# Liq-Glass PG

Specification Sheet (Part/REF # 238515)



The Liq-Glass PG pH Sensor provides an entry level pH sensor that works well in low temperatures and low conductivity applications.

## Product Specifications

<b>Sensor Family</b>	Liq-Glass
<b>Parameter</b>	pH
<b>Sensor Output</b>	Traditional: mV
<b>a-length</b>	120 mm
<b>Electrical Connector</b>	S8
<b>Measurement Principle</b>	Combination electrode; pH potential measured against reference
<b>Measuring Range</b>	pH 1 to 12
<b>Sensitivity</b>	57 to 59 mV / pH at 25 °C
<b>Zero Point</b>	0 ± 20 mV
<b>pH Glass</b>	Hamilton Type F Glass
<b>pH Glass Resistance</b>	Low
<b>Membrane Shape</b>	Spherical
<b>Diaphragm</b>	Ceramic
<b>Number of Diaphragms</b>	3
<b>Electrolyte</b>	Viscous 3 M KCl-LR
<b>Reference System</b>	Hamilton Everef
<b>Liquid Earth</b>	No
<b>Temperature Sensor</b>	No
<b>Diameter</b>	12 mm
<b>Process Connection</b>	PG13,5
<b>Wetted Parts</b>	Glass Ceramic EPDM (Ethylene propylene elastomer)
<b>O-ring Material</b>	FDA 21 CFR 177.2600; EG 1935/2004; USP <87>; USP <88> Class VI (121 °C)
<b>Serial Number</b>	Yes
<b>Recommended Storage</b>	Hamilton Storage Solution or 3 M KCl
<b>Certificate</b>	No
<b>ATEX Approval</b>	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
<b>IECEX Approval</b>	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
<b>Autoclavable</b>	No
<b>CIP</b>	No

---

<b>Steam Sterilizable</b>	No
<b>Operating Temperature Range</b>	-5 to 60 °C
<b>Sample min Conductivity</b>	2 µS/cm
<b>Pressure Range bar g</b>	0 to 2 bar

---

Specifications are subject to change without notice

**Spec. Version B**

<https://www.hamiltoncompany.com/process-analytics/sensors/238515>