

EasyFerm Plus HB K8 325

Specification Sheet (Part/REF # 238633-2553)



The EasyFerm Plus pH sensor is Hamilton's most popular product for pharmaceutical applications where autoclave and SIP are frequently performed.

Product Specifications

Sensor Family	EasyFerm Plus
Parameter	pH
a-length	325 mm
Electrical Connector	K8
Measurement Principle	Combination electrode; pH potential measured against reference
Measuring Range	pH 0 to 14
Sensitivity	57 to 59 mV / pH at 25 °C
Zero Point	0 ± 20 mV
pH Glass	Hamilton type HB glass
pH Glass Resistance	Moderate
Membrane Shape	Spherical
Diaphragm	HP-Coatramic
Number of Diaphragms	1
Electrolyte	Pressurized Phermlyte
Reference System	Hamilton Everef-F, Silver ion barrier included
Liquid Earth	No
Temperature Sensor	No
Diameter	12 mm
Process Connection	PG13,5
Wetted Parts	Glass Ceramic EPDM (Ethylene propylene elastomer)
O-ring Material	FDA 21 CFR 177.2600; EG 1935/2004; USP <87>; USP <88> Class VI (121 °C)
Serial Number	Yes
Recommended Storage	Hamilton Storage Solution or 3 M KCl
Certificate	Yes, with measured values in Buffer pH 4.01 and pH 7.00
ATEX Approval	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
IECEX Approval	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
Autoclavable	Yes
CIP	Yes

Steam Sterilizable	Yes
Operating Temperature Range	0 to 140 °C
Sample min Conductivity	100 µS/cm
Pressure Range bar g	0 to 6 bar

Specifications are subject to change without notice

Spec. Version B

<https://www.hamiltoncompany.com/process-analytics/sensors/238633-2553>