

Accessories Z206-A

Rotor/Bucket

Order No.:
Z206-0650



Angle rotor 6 x 50 ml
Angle: 40°

Adapter

Acceleration in s: 33/95
Deceleration in s: 51/257
max. speed: 6,000 rpm
RCF-value: 4,427 xg
max. radius: 11.0 cm
max. Ø: 29 mm

Order No.:	Tube rack	Ø [mm]	Length (min./max.):
without adapter	1 x 50 ml conical	29	116
without adapter	1 x 50 ml	29	100/120
Z206-50-A15	1 x 15 ml conical	17	120
Z206-50-A57	1 x 7 ml	13	95/115
Z206-50-A57C*	1 x 5 ml	13	65/90

* With Z206-50-A57

Order No.:
Z206-1215



Angle rotor 12 x 15 ml
Angle: 32°

Acceleration in s.: 33/95
Deceleration in s: 51/257
max. speed: 6,000 rpm
RCF-value: 4,427 xg
max. radius: 11.0 cm
max. Ø: 17 mm

Order No.:	Tube rack	Ø [mm]	Length (min./max.):
without adapter	1 x 15 ml conical	17	120
without adapter	1 x 15 ml glass	17	105/120
C3100-ADP	1 x 7 ml	13	95/115
C3100-ADP	1 x 5 ml	13	65/90

Order No.:
Z206-1820



Angle Rotor 18 x 1,5/2,0 ml
Angle: 45°

Acceleration in s: 11/60
Deceleration in s: 10/30
max. speed: 6,000 rpm
RCF-value: 2,938 xg
max. radius: 13.3 cm
max. Ø: 16 mm

Order No.:	Tube Rack	Ø [mm]	Length (min./max.):
C1008-A5-6	1 x 0.5 ml	8.0 mm	45 mm
C1008-A2-6	1 x 0.4/0.2 ml PCR	6.0 mm	45 mm

Order No.:
Z206-0605



Swing out rotor 6 x 5ml blood tube
Angle: 0-90°

Acceleration in s: 8/35
Deceleration in s: 7/25
max. speed: 4,000 rpm
RCF-value: 1,896 xg
max. radius: 10.4 cm

Order No.:
Z206-0457



Swing out rotor 4 x 5-7 ml blood tube
Angle: 0-77°

Acceleration in s: 16/105
Deceleration in s: 12/23
max. speed: 6,000 rpm
RCF-value: 4,467 xg
max. radius: 11.1 cm
max. Ø: 13 mm

www.HermleUSA.com
PH: 908-769-5555
EM: info@benchmarkscientific.com

