

Accessories Z 216 M and Z 216 MK

Rotor/Buckets

Order No.:
Z216-2420



Angle rotor 24 x 1.5/2.0 ml
Angle: 45°

Order No.:
Z216-2420H



Angle rotor 24 x 1.5/2.0 ml
Angle: 45° *Hermetically sealed*

Order No.:
Z216-3020H



Angle rotor 30 x 1.5/2.0 ml
Angle: 45°

Order No.:
Z216-4420



Angle rotor 44 x 1.5/2.0 ml
Angle: 32°/55°

Order No.:
Z216-2420S



COMBI-rotor 24 x 1.5/2.0 ml
and 4 x 8-PCR Strips Angle:
32°/55°

Order No.:
Z216-24SC



Angle rotor 24 x Spin Column Kits
Angle: 45°

Order No.:
Z216-1205



Angle rotor 12 x 5 ml Reaction tubes
Angle: 45°C

Order No.:
Z216-3202



Angle rotor 4 x 8-PCR Strips/32 x .02 ml
Angle: 45°C

Adapter

Acceleration in s: 21/152
Deceleration in s: 18/173
max. speed: 15000 rpm
RCF: 21379 xg
max. radius: 8.5 cm
max. \varnothing : 11 mm
Temp. at max. speed: 4°C

Order No.:	Tube rack	\varnothing (mm)	Length (min./max.)
without	1 x 2.0 ml	11	40
without	1 x 1.5 ml	11	40
C1008-A5-6	1 x 0.5 ml	8	45
C1008-A2-6	1 x 0.4/0.2 ml PCR	6	45

Acceleration in s: 21/151
Deceleration in s: 21/217
max. speed: 15000 rpm
RCF: 21379 xg
max. radius: 8.5 cm
max. \varnothing : 11 mm
Temp. at max. speed: 6°C

Order No.:	Tube rack	\varnothing (mm)	Length (min./max.)
without	1 x 2,0 ml	11	40
without	1 x 1,5 ml	11	40
C1008-A5-6	1 x 0,5 ml	8	45
C1008-A2-6	1 x 0,4/0,2 ml PCR	6	45

Acceleration in s: 29/235
Deceleration in s: 27/258
max. speed: 13500 rpm
RCF: 19151 xg
max. radius: 9.4 cm
max. \varnothing : 11 mm
Temp. at max. speed: 7°C

Order No.:	Tube rack	\varnothing (mm)	Length (min./max.)
without	1 x 2.0 ml	11	40
without	1 x 1.5 ml	11	40
C1008-A5-6	1 x 0.5 ml	8	45
C1008-A2-6	1 x 0.4/0.2 ml PCR	6	45

Acceleration in s: 18/136
Deceleration in s: 17/133
max. speed: 15000 rpm
RCF: 21127 / 21379 xg
max. radius: 8.4 / 8.5 cm
max. \varnothing : 11 mm
Temp. at max. speed: 10°C

Order No.:	Tube rack	\varnothing (mm)	Length (min./max.)
without	1 x 2.0 ml	11	40
without	1 x 1.5 ml	11	40
C1008-A5-6	1 x 0.5 ml	8	45
C1008-A2-6	1 x 0.4/0.2 ml PCR	6	45

Acceleration in s: 18/136
Deceleration in s: 17/133
max. speed: 15000 rpm
RCF: 21127 / 21379 xg
max. radius: 8.4 / 8.5 cm
max. \varnothing : 11 mm
Temp. at max. speed: 10°C

Order No.:	Tube rack	\varnothing (mm)	Length (min./max.)
without	1 x 2.0 ml	11	40
without	1 x 1.5 ml	11	40
C1008-A5-6	1 x 0.5 ml	8	45
C1008-A2-6	1 x 0.4/0.2 ml PCR	6	45

Acceleration in s: 16/137
Deceleration in s: 12/138
max. speed: 13500 rpm
max RCF: 17317 xg
max. radius: 8.5 cm

Order No.:	Tube rack	\varnothing (mm)	Length (min./max.)
C1008-A5-6	1 x 0.5 ml	8	45
C1008-A2-6	1 x 0.4/0.2 ml PCR	6	45

Acceleration in s: 24/148
Deceleration in s: 17/320
max. speed: 14500 rpm
RCF: 19978 xg
max. radius: 8.5 cm
max. \varnothing : 1,7 mm
Temp. at max. speed: 4°C

Order No.:	Adapter
Z216-05-C10	1.0 ml Cryo tubes (\varnothing 12,6 x 41 mm) set of adapters (6 pcs.)
Z216-05-C18	1.8 ml Cryo tubes (\varnothing 12,6 x 48 mm) set of adapters (6 pcs.)

Acceleration in s: 17/150
Deceleration in s: 20/95
max. speed: 15000 rpm
RCF: 15343 xg
max. radius: 6.1 cm
max. \varnothing : 6 mm
Temp. at max. speed: 2,5°C