

Accessories Z327 and Z327-K

Rotor/Bucket

Order No.:
Z327-200

Swing out rotor 4 place w/ buckets
Angle: 0-90°
(w/o buckets: Z327-200-AC)

Z327-200-BUK
Bucket for Adapter

Z327-200-LID
Lid for Bucket | hermetically sealed



Adapter

Acceleration in s: 21/102
Deceleration in s: 12/387
max. speed: 5,000 rpm
RCF-Value: 4,136 xg
max. radius: 14.8 cm

Volume

Tubes Ø in mm

200 ml
bottle
56

200 ml
conical
56

100 ml
RB Glass
40

85 ml
RB/OR
38



Length min./max. (mm)

Tubes per Rotor

Radius Correction (cm)

Order No. Adapter: Z327-200-___

112

120

95/115

95/108

4

4

4

4

0.0

0.0

0.2

0.2

without

A200

A100

A85

Volume

Tubes Ø in mm

50 ml

RB/OR

29

50 ml

conical

29

50 ml

skirted

29

25/30 ml

Universal

25

25/30 ml

RB/OR

25

15 ml

conical

17

15 ml

conical

17

15 ml

RB

17

5/7 ml

RB

13

5 ml

conical

17

1.5/2.0 ml

micro

11

6-10 ml

Vakut.®

16

6-10 ml

Vakut.®

16

1.8-7 ml

Vakut.®

13

50 ml

conical

29



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter: Z327-200-___

95/103

116

116

95/105

90/110

120

120

60/107

65/100

60/70

40

130

100

75/100

116

4

4

4

4

4

16

12

28

32

20

32

4

28

32

8

0.2

0.1

0.2

0.2

0.1

0.0

0.0

0.2

0.2

0.1

0.1

0.2

0.2

0.2

0.0

A50R

A50

A50SS

A25

A30

A15B*

A15

A15R

A57

A5F

A20

A15L

A10

A57

B50

*only without bucket lid

Order No.:
Z306-100



Swing out rotor 4 place
Angle: 0-90°

Acceleration in s: 12/93
Deceleration in s: 12/226
max. speed: 4,500 rpm
RCF-Value: 3,350 xg
max. radius: 14.8 cm

Volume

Tubes Ø in mm

145 ml
Nalgene®
50

100 ml
RB Glass
44

85 ml
RB/OR
38

50 ml
RB Glass
29

50 ml
conical
29



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter: Z306-100-___

100

90/108

90/108

90/118

116

4

4

4

4

4

1.0

1.0

0.8

0.7

0.3

A145

A100

A85

A50R

A50

Volume

Tubes Ø in mm

50 ml

Rim

29

30 ml

Universal

25

15 ml

conical

17

15 ml

RB

17

6-10 ml

Vakut.®

16

1.8-7 ml

Vakut.®

13

1.5/2.0 ml

micro

11



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter

116

95/105

120

90/108

90/108

75/100

40

4

4

8

28

28

28

40

0.6

1.1

0.0

0.4

0.4

0.7

5.5

A50SS

A30

A15

A10

A10

A57

A20

Order No.:
Z326-100H

Swing out rotor 4 Places
w/ sealed buckets
Angle: 0-90°

Z326-100H-BUK
Bucket for Tube Rack w/ lid

Z326-100H-LID
Lid for bucket



Acceleration in s: 15/100
Deceleration in s: 15/150
max. Speed: 5000 rpm
RCF-value: 4080 xg
max. Radius: 14.6 cm
Temp. at max. speed: 2°C

Volume

Tubes ø in mm

100 ml
RB Glass
40

85 ml
RB/OR
38

50 ml
RB/OR
29

50 ml
Falcon®
29



Length min./max. in mm

Tubes per rotor

Radius correction (cm)

Order-No.: Z326-100H-___

90/108

90/108

90/133

116