

# Accessories Z327 and Z327-K

## Rotor/Bucket

Order No.:  
**Z327-200**

Swing out rotor 4 place w/ buckets  
Angle: 0-90°  
(w/o buckets: Z327-200-AC)

Z327-200-BUK  
Bucket for Adapter


Z327-200-LID  
Lid for Bucket | hermetically sealed



## Adapter

Acceleration in s: 21/102  
Deceleration in s: 12/387  
max. speed: 5,000 rpm  
RCF-Value: 4,136 xg  
max. radius: 14.8 cm

Volume  
Tubes Ø in mm



Length min./max. (mm)  
Tubes per Rotor  
Radius Correction (cm)  
Order No. Adapter: Z327-200-\_\_\_

200ml bottle	200ml conical	100ml RB Glass	85ml RB/OR
56	56	40	38
112	120	95/115	95/108
4	4	4	4
0.0	0.0	0.2	0.2
without	A200	A100	A85

Volume  
Tubes Ø in mm

Length min./max. (mm)  
Tubes per rotor  
Radius Correction (cm)  
Order No. Adapter: Z327-200-\_\_\_

50 ml RB/OR	50 ml conical	50 ml skirted	25/30 ml Universal	25/30 ml RB/OR	15 ml conical	15 ml conical	15 ml RB	5/7 ml RB	5 ml conical	1.5/2.0 ml micro	6-10 ml Vakut.®	6-10 ml Vakut.®	1.8-7 ml Vakut.®	50 ml conical
29	29	29	25	25	17	17	17	13	17	11	16	16	13	29
95/103	116	116	95/105	90/110	120	120	60/107	65/100	60/70	40	130	100	75/100	116
4	4	4	4	4	16	12	28	32	20	32	4	28	32	8
0.2	0.1	0.2	0.2	0.2	0.1	0.0	0.2	0.2	0.1	0.1	0.2	0.2	0.2	0.0
A50R	A50	A50SS	A25	A30	A15B*	A15	A15R	A57	A5F	A20	A15L	A10	A57	B50

\*only without bucket lid


Order No.:  
**Z306-100**

Swing out rotor 4 place  
Angle: 0-90°



Acceleration in s: 12/93  
Deceleration in s: 12/226  
max. speed: 4,500 rpm  
RCF-Value: 3,350 xg  
max. radius: 14.8 cm

Volume  
Tubes Ø in mm



Length min./max. (mm)  
Tubes per rotor  
Radius Correction (cm)  
Order No. Adapter: Z306-100-\_\_\_

145 ml Nalgene®	100 ml RB Glass	85 ml RB/OR	50 ml RB Glass	50 ml conical
50	44	38	29	29
100	90/108	90/108	90/118	116
4	4	4	4	4
1.0	1.0	0.8	0.7	0.3
A145	A100	A85	A50R	A50

Volume  
Tubes Ø in mm

Length min./max. (mm)  
Tubes per rotor  
Radius Correction (cm)  
Order No. Adapter

50 ml Rim	30 ml Universal	15 ml conical	15 ml RB	6-10 ml Vakut.®	1.8-7 ml Vakut.®	1.5/2.0 ml micro
29	25	17	17	16	13	11
116	95/105	120	90/108	90/108	75/100	40
4	4	8	28	28	28	40
0.6	1.1	0.0	0.4	0.4	0.7	5.5
A50SS	A30	A15	A10	A10	A57	A20

Order No.:  
**Z326-100H**

Swing out rotor 4 Places  
w/ sealed buckets  
Angle: 0-90°


Z326-100H-BUK  
Bucket for Tube Rack w/ lid

Z326-100H-LID  
Lid for bucket



Acceleration in s: 15/100  
Deceleration in s: 15/150  
max. Speed: 5000 rpm  
RCF-value: 4080 xg  
max. Radius: 14.6 cm  
Temp. at max. speed: 2°C

Volume  
Tubes ø in mm



Length min./max. in mm  
Tubes per rotor  
Radius correction (cm)  
Order-No.: Z326-100H-\_\_\_

100 ml RB Glass	85 ml RB/OR	50 ml RB/OR	50 ml Falcon®
40	38	29	29
90/108	90/108	90/133	116
4	4	4	4
0.9	0.6	0.6	0.4
A100	A85	A50R	A50

Volume  
Tubes Ø in mm

Length min./max. (mm)  
Tubes per rotor  
Radius Correction (cm)  
Order No. Tube rack

50 ml skirted	30 ml Universal	15 ml Falcon®	15 ml Falcon®	15 ml RB Glass	6-10 ml Vakut.®	10-15 ml Vakut.®	1.8-7 ml Vakut.®	1.5 ml Reakt.	50 ml Falcon®	15 ml Falcon®
29	25	17	17	17	16	16	13	11	29	17
116	95/105	120	120	90/108	75/100	75/125	75/100	42	116	120
4	4	4	8	16	16	4	16	20	8	12
0.7	1.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.0	0.0
A50SS	A30	A15S	A15*	A15R	A10	A15L*	A57	A20	B50	B15

\* only without bucket lid