

Accessories Z327 and Z327-K

Rotor/Bucket

Order No.:
Z327-200

Swing out rotor 4 place w/ buckets
Angle: 0-90°
(w/o buckets: Z327-200-AC)

Z327-200-BUK
Bucket for Adapter

Z327-200-LID
Lid for Bucket | hermetically sealed



Adapter

Acceleration in s: 21/102
Deceleration in s: 12/387
max. speed: 5,000 rpm
RCF-Value: 4,136 xg
max. radius: 14.8 cm

Volume

Tubes Ø in mm

200 ml
bottle
56

200 ml
conical
56

100 ml
RB Glass
40

85 ml
RB/OR
38



Length min./max. (mm)

Tubes per Rotor

Radius Correction (cm)

Order No. Adapter: Z327-200-___

112
4
0.0
without

120
4
0.0
A200

95/115
4
0.2
A100

95/108
4
0.2
A85

Volume

Tubes Ø in mm

50 ml
RB/OR
29

50 ml
conical
29

50 ml
skirted
29

25/30 ml
Universal
25

25/30 ml
RB/OR
25

15 ml
conical
17

15 ml
conical
17

15 ml
RB
17

5/7 ml
RB
13

5 ml
conical
17

1.5/2.0 ml
micro
11

6-10 ml
Vakut.®
16

6-10 ml
Vakut.®
16

1.8-7 ml
Vakut.®
13

50 ml
conical
29



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter: Z327-200-___

95/103
4
0.2
A50R

116
4
0.1
A50

116
4
0.2
A50SS

95/105
4
0.2
A25

90/110
4
0.2
A30

120
16
0.1
A15B*

120
12
0.0
A15

60/107
28
0.2
A15R

65/100
32
0.2
A57

60/70
20
0.1
A5F

40
32
0.1
A20

130
4
0.2
A15L

100
28
0.2
A10

75/100
32
0.2
A57

116
8
0.0
B50

Order No.:
Z306-100

Swing out rotor 4 place
Angle: 0-90°



Acceleration in s: 12/93
Deceleration in s: 12/226
max. speed: 4,500 rpm
RCF-Value: 3,350 xg
max. radius: 14.8 cm

Volume

Tubes Ø in mm

145 ml
Nalgene®
50

100 ml
RB Glass
44

85 ml
RB/OR
38

50 ml
RB Glass
29

50 ml
conical
29



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter: Z306-100-___

100
4
1.0
A145

90/108
4
1.0
A100

90/108
4
0.8
A85

90/118
4
0.7
A50R

116
4
0.3
A50

Volume

Tubes Ø in mm

50 ml
Rim
29

30 ml
Universal
25

15 ml
conical
17

15 ml
RB
17

6-10 ml
Vakut.®
16

1.8-7 ml
Vakut.®
13

1.5/2.0 ml
micro
11



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter

116
4
0.6
A50SS

95/105
4
1.1
A30

120
8
0.0
A15

90/108
28
0.4
A10

90/108
28
0.4
A10

75/100
28
0.7
A57

40
40
5.5
A20

Order No.:
Z326-100H

Swing out rotor 4 Places
w/ sealed buckets
Angle: 0-90°

Z326-100H-BUK
Bucket for Tube Rack w/ lid

Z326-100H-LID
Lid for bucket



Acceleration in s: 15/100
Deceleration in s: 15/150
max. Speed: 5000 rpm
RCF-value: 4080 xg
max. Radius: 14.6 cm
Temp. at max. speed: 2°C

Volume

Tubes ø in mm

100 ml
RB Glass
40

85 ml
RB/OR
38

50 ml
RB/OR
29

50 ml
Falcon®
29



Length min./max. in mm

Tubes per rotor

Radius correction (cm)

Order-No.: Z326-100H-___

90/108
4
0.9
A100

90/108
4
0.6
A85

90/133
4
0.6
A50R

116
4
0.4
A50

Volume

Tubes Ø in mm

50 ml
skirted
29

30 ml
Universal
25

15 ml
Falcon®
17

15 ml
Falcon®
17

15 ml
RB Glass
17

6-10 ml
Vakut.®
16

10-15 ml
Vakut.®
16

1.8-7 ml
Vakut.®
13

1.5 ml
Reakt.
11

50 ml
Falcon®
29

15 ml
Falcon®
17



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Tube rack

116
4
0.7
A50SS

95/105
4
1.5
A30

120
4
0.5
A15S

120
8
0.5
A15*

90/108
16
0.6
A15R

75/100
16
0.6
A10

75/125
4
0.6
A15L*

75/100
16
0.6
A57

42
20
0.6
A20

116
8
0.0
B50

120
12
0.0
B15

* only without bucket lid