

# Accessories Z327 and Z327-K

## Rotor/Adapter

Order No.:  
Z327-200

Swing out rotor 4 place w/ buckets  
Angle: 0-90°  
(w/o buckets: Z327-200-AC)

Z327-200-BUK  
Bucket for Adapter

Z327-200-LID  
Lid for Bucket | hermetically sealed



## Adapter

Acceleration in s: 21/102  
Deceleration in s: 12/387  
max. speed: 5,000 rpm  
RCF-Value: 4,136 xg  
max. radius: 14.8 cm

Volume  
Tubes Ø in mm

Length min./max. (mm)  
Tubes per Rotor  
Radius Correction (cm)  
Order No. Adapter: Z327-200-\_\_\_

Volume	200 ml bottle 56	200 ml conical 56	100 ml RB Glass 40	85 ml RB/OR 38
Length min./max. (mm)	112	120	95/115	95/108
Tubes per Rotor	4	4	4	4
Radius Correction (cm)	0.0	0.0	0.2	0.2
Order No. Adapter: Z327-200-___	without	A200	A100	A85

Volume	50 ml RB/OR 29	50 ml conical 29	50 ml skirted 29	25/30 ml Universal 25	25/30 ml RB/OR 25	15 ml conical 17	15 ml conical 17	15 ml RB 17	5/7 ml RB 13	5 ml conical 17	1.5/2.0 ml micro 11	6-10 ml Vakut. <sup>®</sup> 16	6-10 ml Vakut. <sup>®</sup> 16	1.8-7 ml Vakut. <sup>®</sup> 13	50 ml conical 29
Tubes Ø in mm	29	29	29	25	25	17	17	17	13	17	11	16	16	13	29
Length min./max. (mm)	95/103	116	116	95/105	90/110	120	120	60/107	65/100	60/70	40	130	100	75/100	116
Tubes per rotor	4	4	4	4	4	16	12	28	32	20	32	4	28	32	8
Radius Correction (cm)	0.2	0.1	0.2	0.2	0.2	0.1	0.0	0.2	0.2	0.1	0.1	0.2	0.2	0.2	0.0
Order No. Adapter: Z327-200-___	A50R	A50	A50SS	A25	A30	A15B*	A15	A15R	A57	A5F	A20	A15L	A10	A57	B50

\*only without bucket lid

Order No.:  
Z306-100

Swing out rotor 4 place  
Angle: 0-90°



Acceleration in s: 12/93  
Deceleration in s: 12/226  
max. speed: 4,500 rpm  
RCF-Value: 3,350 xg  
max. radius: 14.8 cm

Volume  
Tubes Ø in mm

Length min./max. (mm)  
Tubes per rotor  
Radius Correction (cm)  
Order No. Adapter: Z306-100-\_\_\_

Volume	145 ml Nalgene <sup>®</sup> 50	100 ml RB Glass 44	85 ml RB/OR 38	50 ml RB Glass 29	50 ml conical 29
Length min./max. (mm)	100	90/108	90/108	90/118	116
Tubes per rotor	4	4	4	4	4
Radius Correction (cm)	1.0	1.0	0.8	0.7	0.3
Order No. Adapter: Z306-100-___	A145	A100	A85	A50R	A50

Volume	50 ml Rim 29	30 ml Universal 25	15 ml conical 17	15 ml RB 17	6-10 ml Vakut. <sup>®</sup> 16	1.8-7 ml Vakut. <sup>®</sup> 13	1.5/2.0 ml micro 11
Tubes Ø in mm	29	25	17	17	16	13	11
Length min./max. (mm)	116	95/105	120	90/108	90/108	75/100	40
Tubes per rotor	4	4	8	28	28	28	40
Radius Correction (cm)	0.6	1.1	0.0	0.4	0.4	0.7	5.5
Order No. Adapter	A50SS	A30	A15	A10	A10	A57	A20

Order No.:  
Z326-100H

Swing out rotor 4 Places  
w/ sealed buckets  
Angle:0-90°

Z326-100H-BUK  
Bucket for Tube Rack w/ lid

Z326-100H-LID  
Lid for bucket



Acceleration in s: 15/100  
Deceleration in s: 15/150  
max. Speed: 5000 rpm  
RCF-value: 4080 xg  
max. Radius: 14.6 cm  
Temp. at max. speed: 2°C

Volume  
Tubes ø in mm

Length min./max. in mm  
Tubes per rotor  
Radius correction (cm)  
Order-No.: Z326-100H-\_\_\_

Volume	100 ml RB Glass 40	85 ml RB/OR 38	50 ml RB/OR 29	50 ml Falcon <sup>®</sup> 29
Length min./max. in mm	90/108	90/108	90/133	116
Tubes per rotor	4	4	4	4
Radius correction (cm)	0.9	0.6	0.6	0.4
Order-No.: Z326-100H-___	A100	A85	A50R	A50

Volume	50 ml skirted 29	30 ml Universal 25	15 ml Falcon <sup>®</sup> 17	15 ml Falcon <sup>®</sup> 17	15 ml RB Glass 17	6-10 ml Vakut. <sup>®</sup> 16	10-15ml Vakut. <sup>®</sup> 16	1.8-7 ml Vakut. <sup>®</sup> 13	1.5 ml Reakt. 11	50ml Falcon <sup>®</sup> 29	15ml Falcon <sup>®</sup> 17
Tubes Ø in mm	29	25	17	17	17	16	16	13	11	29	17
Length min./max. (mm)	116	95/105	120	120	90/108	75/100	75/125	75/100	42	116	120
Tubes per rotor	4	4	4	8	16	16	4	16	20	8	12
Radius Correction (cm)	0.7	1.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.0	0.0
Order No. Tube rack	A50SS	A30	A15S	A15*	A15R	A10	A15L*	A57	A20	B50	B15

\* only without bucket lid