

# Accessories Z327 and Z327-K

## Rotor/Bucket

Order No.:  
**Z327-200**

Swing out rotor 4 place w/ buckets  
Angle: 0-90°  
(w/o buckets: Z327-200-AC)

Z327-200-BUK  
Bucket for Adapter

Z327-200-LID  
Lid for Bucket | hermetically sealed



## Adapter

Acceleration in s: 21/102  
Deceleration in s: 12/387  
max. speed: 5,000 rpm  
RCF-Value: 4,136 xg  
max. radius: 14.8 cm

Volume

Tubes Ø in mm

200 ml  
bottle  
56

200 ml  
conical  
56

100 ml  
RB Glass  
40

85 ml  
RB/OR  
38



Length min./max. (mm)

Tubes per Rotor

Radius Correction (cm)

Order No. Adapter: Z327-200-\_\_\_

112

120

95/115

95/108

4

4

4

4

0.0

0.0

0.2

0.2

without

A200

A100

A85

Volume

Tubes Ø in mm

50 ml  
RB/OR  
29

50 ml  
conical  
29

50 ml  
skirted  
29

25/30 ml  
Universal  
25

25/30 ml  
RB/OR  
25

15 ml  
conical  
17

15 ml  
conical  
17

15 ml  
RB  
17

5/7 ml  
RB  
13

5 ml  
conical  
17

1.5/2.0 ml  
micro  
11

6-10 ml  
Vakut.®  
16

6-10 ml  
Vakut.®  
16

1.8-7 ml  
Vakut.®  
13

50 ml  
conical  
29



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter: Z327-200-\_\_\_

95/103

116

116

95/105

90/110

120

120

60/107

65/100

60/70

40

130

100

75/100

116

4

4

4

4

4

16

12

28

32

20

32

4

28

32

8

0.2

0.1

0.2

0.2

0.1

0.0

0.0

0.2

0.2

0.1

0.1

0.2

0.2

0.2

0.0

A50R

A50

A50SS

A25

A30

A15B\*

A15

A15R

A57

A5F

A20

A15L

A10

A57

B50

\*only without bucket lid

Order No.:  
**Z306-100**



Swing out rotor 4 place  
Angle: 0-90°

Acceleration in s: 12/93  
Deceleration in s: 12/226  
max. speed: 4,500 rpm  
RCF-Value: 3,350 xg  
max. radius: 14.8 cm

Volume

Tubes Ø in mm

145 ml  
Nalgene®  
50

100 ml  
RB Glass  
44

85 ml  
RB/OR  
38

50 ml  
RB Glass  
29

50 ml  
conical  
29



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter: Z306-100-\_\_\_

100

90/108

90/108

90/118

116

4

4

4

4

4

1.0

1.0

0.8

0.7

0.3

A145

A100

A85

A50R

A50

Volume

Tubes Ø in mm

50 ml  
Rim  
29

30 ml  
Universal  
25

15 ml  
conical  
17

15 ml  
RB  
17

6-10 ml  
Vakut.®  
16

1.8-7 ml  
Vakut.®  
13

1.5/2.0 ml  
micro  
11



Length min./max. (mm)

Tubes per rotor

Radius Correction (cm)

Order No. Adapter

116

95/105

120

90/108

90/108

75/100

40

4

4

8

28

28

28

40

0.6

1.1

0.0

0.4

0.4

0.7

5.5

A50SS

A30

A15

A10

A10

A57

A20

Order No.:  
**Z326-100H**

Swing out rotor 4 Places  
w/ sealed buckets  
Angle: 0-90°

Z326-100H-BUK  
Bucket for Tube Rack w/ lid

Z326-100H-LID  
Lid for bucket



Acceleration in s: 15/100  
Deceleration in s: 15/150  
max. Speed: 5000 rpm  
RCF-value: 4080 xg  
max. Radius: 14.6 cm  
Temp. at max. speed: 2°C

Volume

Tubes ø in mm

100 ml  
RB Glass  
40

85 ml  
RB/OR  
38

50 ml  
RB/OR  
29

50 ml  
Falcon®  
29



Length min./max. in mm

Tubes per rotor

Radius correction (cm)

Order-No.: Z326-100H-\_\_\_

90/108

90/108

90/133

116

4

4

4

4

0.9

0.6

0.6

0.4

A100

A85

A50R

A50

Volume

Tubes Ø in mm

50 ml  
skirted  
29

30 ml  
Universal  
25

15 ml  
Falcon®  
17

15 ml  
Falcon®  
17

15 ml  
RB Glass  
17

6-10 ml  
Vakut.®  
16

10-15 ml  
Vakut.®  
16

1.8-7 ml  
Vakut.®  
13

1.5 ml  
Reakt.  
11

50 ml  
Falcon®  
29

15 ml  
Falcon®  
17

