

Accessories Z327 and Z327-K

Rotor/Bucket

Order No.:
Z327-200

Swing out rotor 4 place w/ buckets
Angle: 0-90°
(w/o buckets: Z327-200-AC)



Z327-200-BUK
Bucket for Adapter

Z327-200-LID
Lid for Bucket | hermetically sealed

Adapter

Acceleration in s: 21/102
Deceleration in s: 12/387
max. speed: 5,000 rpm
RCF-Value: 4,136 xg
max. radius: 14.8 cm

Volume
Tubes Ø in mm

200 ml bottle 56	200 ml conical 56	100 ml RB Glass 40	85 ml RB/OR 38

Length min./max. (mm)
Tubes per Rotor
Radius Correction (cm)
Order No. Adapter: Z327-200-___

112	120	95/115	95/108
4	4	4	4
0.0	0.0	0.2	0.2
without	A200	A100	A85

Volume
Tubes Ø in mm

50 ml RB/OR 29	50 ml conical 29	50 ml skirted 29	25/30 ml Universal 25	25/30 ml RB/OR 25	15 ml conical 17	15 ml conical 17	15 ml RB 17	5/7 ml RB 13	5 ml conical 17	1.5/2.0 ml micro 11	6-10 ml Vakut.® 16	6-10 ml Vakut.® 16	1.8-7 ml Vakut.® 13	50 ml conical 29
95/103	116	116	95/105	90/110	120	120	60/107	65/100	60/70	40	130	100	75/100	116
4	4	4	4	4	16	12	28	32	20	32	4	28	32	8
0.2	0.1	0.2	0.2	0.2	0.1	0.0	0.2	0.2	0.1	0.1	0.2	0.2	0.2	0.0
A50R	A50	A50SS	A25	A30	A15B*	A15	A15R	A57	A5F	A20	A15L	A10	A57	B50

Length min./max. (mm)
Tubes per rotor
Radius Correction (cm)
Order No. Adapter: Z327-200-___

Order No.:
Z306-100



Swing out rotor 4 place
Angle: 0-90°

Acceleration in s: 12/93
Deceleration in s: 12/226
max. speed: 4,500 rpm
RCF-Value: 3,350 xg
max. radius: 14.8 cm

Volume
Tubes Ø in mm

145 ml Nalgene® 50	100 ml RB Glass 44	85 ml RB/OR 38	50 ml RB Glass 29	50 ml conical 29

Length min./max. (mm)
Tubes per rotor
Radius Correction (cm)
Order No. Adapter: Z306-100-___

100	90/108	90/108	90/118	116
4	4	4	4	4
1.0	1.0	0.8	0.7	0.3
A145	A100	A85	A50R	A50

Volume
Tubes Ø in mm

50 ml Rim 29	30 ml Universal 25	15 ml conical 17	15 ml RB 17	6-10 ml Vakut.® 16	1.8-7 ml Vakut.® 13	1.5/2.0 ml micro 11
116	95/105	120	90/108	90/108	75/100	40
4	4	8	28	28	28	40
0.6	1.1	0.0	0.4	0.4	0.7	5.5
A50SS	A30	A15	A10	A10	A57	A20

Length min./max. (mm)
Tubes per rotor
Radius Correction (cm)
Order No. Adapter

Order No.:
Z326-100H

Swing out rotor 4 Places
w/ sealed buckets
Angle: 0-90°

Z326-100H-BUK
Bucket for Tube Rack w/ lid

Z326-100H-LID
Lid for bucket



Acceleration in s: 15/100
Deceleration in s: 15/150
max. Speed: 5000 rpm
RCF-value: 4080 xg
max. Radius: 14.6 cm
Temp. at max. speed: 2°C

Volume
Tubes Ø in mm

100 ml RB Glass 40	85 ml RB/OR 38	50 ml RB/OR 29	50 ml Falcon® 29

Length min./max. in mm
Tubes per rotor
Radius correction (cm)
Order-No.: Z326-100H-___

90/108	90/108	90/133	116
4	4	4	4
0.9	0.6	0.6	0.4
A100	A85	A50R	A50

Volume
Tubes Ø in mm

50 ml skirted 29	30 ml Universal 25	15 ml Falcon® 17	15 ml Falcon® 17	15 ml RB Glass 17	6-10 ml Vakut.® 16	10-15 ml Vakut.® 16	1.8-7 ml Vakut.® 13	1.5 ml Reakt. 11	50 ml Falcon® 29	15 ml Falcon® 17
116	95/105	120	120	90/108	75/100	75/125	75/100	42	116	120
4	4	4	8	16	16	4	16	20	8	12
0.7	1.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.0	0.0
A50SS	A30	A15S	A15*	A15R	A10	A15L*	A57	A20	B50	B15

Length min./max. (mm)
Tubes per rotor
Radius Correction (cm)
Order No. Tube rack

* only without bucket lid